

03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** 03F - UNILAK ALL-PURPOSE SATIN ENAMEL
White and colours, Base White W1, Base Neutral
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Enamel
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Industrias Titán, S.A.U.
Pol. Ind. Pratense, calle 114 nº 17-19
08820 El Prat de Llobregat - Barcelona - España
Phone.: +34 934 797 494 - Fax: +34 934 797 495
msds@titanlux.es
http://www.titanlux.es
- 1.4 Emergency telephone number:** +34 934 797 494 (7:30-14:30 h.) (working hours)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Hazard statements:
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects
Precautionary statements:
P101: If medical advice is needed, have product container or label at hand
P102: Keep out of reach of children
P273: Avoid release to the environment
P501: Dispose of contents/container according to the separated collection system used in your municipality
Supplementary information:
EUH208: Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**
Non-applicable
- 3.2 Mixture:**
Chemical description: Aqueous mixture composed of additives, aggregates, pigments and resins
Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:





Identification	Chemical name/Classification	Concentration
CAS: 65143-89-7 EC: 405-430-6 Index: Non-applicable REACH: 01-0000015495-66-XXXX	Benzenesulfonic acid, hexadecyl (sulfophenoxy)-, sodium salt (1:2)⁽¹⁾ Self-classified Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318 - Danger	0,4 - <0,5 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Substance with a Union workplace exposure limit

03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Chemical name/Classification	Concentration
CAS: 111-77-3 EC: 203-906-6 Index: 603-107-00-6 REACH: 01-2119475100-52-XXXX	2-(2-methoxyethoxy)ethanol⁽¹⁾ Regulation 1272/2008 Repr. 2: H361d - Warning	ATP CLP00  0,2 - <0,3 %
CAS: 2634-33-5 EC: 220-120-9 Index: 613-088-00-6 REACH: 01-2120761540-60-XXXX	1,2-benzisothiazol-3(2H)-one⁽¹⁾ Regulation 1272/2008 Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	ATP CLP00  0,02 - <0,03 %
CAS: 34123-59-6 EC: 251-835-4 Index: 006-044-00-7 REACH: Non-applicable	Isoproturon⁽¹⁾ Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Carc. 2: H351; STOT RE 2: H373 - Warning	ATP ATP13  0,01 - <0,02 %
CAS: 112-34-5 EC: 203-961-6 Index: 603-096-00-8 REACH: 01-2119475104-44-XXXX	2-(2-butoxyethoxy)ethanol⁽²⁾ Regulation 1272/2008 Eye Irrit. 2: H319 - Warning	ATP CLP00  <0,01 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830
⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

- CONTINUED ON NEXT PAGE -

03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.:	5 °C
Maximum Temp.:	40 °C
Maximum time:	36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

- CONTINUED ON NEXT PAGE -

03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

Identification	Environmental limits		
	IOELV (8h)	IOELV (STEL)	
2-(2-methoxyethoxy)ethanol CAS: 111-77-3 EC: 203-906-6	10 ppm		50.1 mg/m ³
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	10 ppm		67.5 mg/m ³
	15 ppm		101.2 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-(2-methoxyethoxy)ethanol CAS: 111-77-3 EC: 203-906-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,53 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	50,1 mg/m ³	Non-applicable
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	101,2 mg/m ³	67,5 mg/m ³	67,5 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-(2-methoxyethoxy)ethanol CAS: 111-77-3 EC: 203-906-6	Oral	Non-applicable	Non-applicable	1,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,27 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	25 mg/m ³	Non-applicable
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Non-applicable	Non-applicable	1,25 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	50 mg/kg	Non-applicable
	Inhalation	Non-applicable	50,6 mg/m ³	40,5 mg/m ³	34 mg/m ³

PNEC:

Identification		Environmental limits		
		STP	Soil	Intermittent
2-(2-methoxyethoxy)ethanol CAS: 111-77-3 EC: 203-906-6	Fresh water	10000 mg/L		12 mg/L
	Marine water	2,44 mg/kg		1,2 mg/L
	Sediment (Fresh water)	12 mg/L		44,4 mg/kg
	Sediment (Marine water)	90 g/kg		0,44 mg/kg
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Fresh water	200 mg/L		1 mg/L
	Marine water	0,32 mg/kg		0,1 mg/L
	Sediment (Fresh water)	11 mg/L		4 mg/kg
	Sediment (Marine water)	56 g/kg		0,4 mg/kg



8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
	Filter mask for particles		EN 149:2001+A1:2009	Replace when an increase in resistance to breathing is observed.

C.- Specific protection for the hands

- CONTINUED ON NEXT PAGE -



03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"



D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0,3 % weight
V.O.C. density at 20 °C:	3,97 kg/m ³ (3,97 g/L)
Average carbon number:	4,98
Average molecular weight:	120 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C:	105 kg/m ³ (105 g/L)
EU limit for the product (Cat. A.D):	130 g/L (2010)
Components:	Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	Not available
Odour:	Characteristic
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	109 °C
Vapour pressure at 20 °C:	2281 Pa
Vapour pressure at 50 °C:	12018,72 Pa (12,02 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	1080 - 1320 kg/m ³
Relative density at 20 °C:	1,08 - 1,32
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Flammability:	
Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	189 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
Explosive:	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
9.2 Other information:	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

- CONTINUED ON NEXT PAGE -

03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 10: STABILITY AND REACTIVITY (continued)

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
IARC: Formaldehyde (1); Titanium dioxide (2B); Talc (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

- CONTINUED ON NEXT PAGE -

03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Benzenesulfonic acid, hexadecyl (sulfophenoxy)-, sodium salt (1:2) CAS: 65143-89-7 EC: 405-430-6	5500 mg/kg	Non-applicable	Rat
	Non-applicable	Non-applicable	
	Non-applicable	Non-applicable	
2-(2-methoxyethoxy)ethanol CAS: 111-77-3 EC: 203-906-6	7128 mg/kg	9404 mg/kg	Rat
	9404 mg/kg	Non-applicable	Rabbit
	Non-applicable	Non-applicable	
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	500 mg/kg	Non-applicable	Rat
	Non-applicable	Non-applicable	
	Non-applicable	Non-applicable	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Species	Genus
	LC50	EC50		
Benzenesulfonic acid, hexadecyl (sulfophenoxy)-, sodium salt (1:2) CAS: 65143-89-7 EC: 405-430-6	0.42 mg/L (96 h)		Oncorhynchus mykiss	Fish
	14 mg/L (48 h)		Daphnia magna	Crustacean
	42 mg/L (72 h)		Pseudokirchneriella subcapitata	Algae
2-(2-methoxyethoxy)ethanol CAS: 111-77-3 EC: 203-906-6	5741 mg/L (96 h)		Pimephales promelas	Fish
	1192 mg/L (48 h)		Daphnia magna	Crustacean
	Non-applicable			
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	0.1 - 1 mg/L (96 h)			Fish
	0.1 - 1 mg/L			Crustacean
	0.1 - 1 mg/L			Algae
Isoproturon CAS: 34123-59-6 EC: 251-835-4	0.1 - 1 mg/L (96 h)			Fish
	0.1 - 1 mg/L			Crustacean
	0.1 - 1 mg/L			Algae
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	1300 mg/L (96 h)		Lepomis macrochirus	Fish
	2850 mg/L (24 h)		Daphnia magna	Crustacean
	53 mg/L (192 h)		Microcystis aeruginosa	Algae

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
	BOD5	COD	Concentration	Period
Benzenesulfonic acid, hexadecyl (sulfophenoxy)-, sodium salt (1:2) CAS: 65143-89-7 EC: 405-430-6	Non-applicable	Non-applicable	20 mg/L	7 days
	Non-applicable	Non-applicable		
	Non-applicable	Non-applicable	% Biodegradable	95 %

- CONTINUED ON NEXT PAGE -

03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
2-(2-methoxyethoxy)ethanol CAS: 111-77-3 EC: 203-906-6	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	0.07	% Biodegradable	100 %
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	BOD5	0.25 g O2/g	Concentration	100 mg/L
	COD	2.08 g O2/g	Period	28 days
	BOD5/COD	0.12	% Biodegradable	92 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	Parameter	Value
2-(2-methoxyethoxy)ethanol CAS: 111-77-3 EC: 203-906-6	BCF	3
	Pow Log	-1.18
	Potential	Low
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	BCF	2
	Pow Log	1.45
	Potential	Low
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	BCF	0.46
	Pow Log	0.56
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Parameter	Value	Parameter	Value
2-(2-methoxyethoxy)ethanol CAS: 111-77-3 EC: 203-906-6	Koc	1	Henry	1,621E-6 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Non-applicable
	Surface tension	3,59E-2 N/m (25 °C)	Moist soil	No
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Koc	48	Henry	7,2E-9 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	No
	Surface tension	3,395E-2 N/m (25 °C)	Moist soil	No

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 1,2-benzisothiazol-3(2H)-one, (ethylenedioxy)dimethanol, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), Carbendazim (ISO), Isoproturon, 3-iodo-2-propynyl Butylcarbamate, Terbutryn, Tetrahydro-1,3,4,6-tetrakis (hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione, 2-methyl-2H-isothiazol-3-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 10, 11, 12, 13) ; Isoproturon (Product-type 7, 10)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ...):

Contains more than 0.1 % of 2-(2-methoxyethoxy)ethanol by weight. Shall not be placed on the market after 27 June 2010, for supply to the general public, as a constituent of paints, paint strippers, cleaning agents, selfshining emulsions or floor sealants in concentrations equal to or greater than 0,1 % by weight.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

03F - UNILAK ALL-PURPOSE SATIN ENAMEL White and colours, Base White W1, Base Neutral

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 4: H302 - Harmful if swallowed
Aquatic Acute 1: H400 - Very toxic to aquatic life
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects
Carc. 2: H351 - Suspected of causing cancer
Eye Dam. 1: H318 - Causes serious eye damage
Eye Irrit. 2: H319 - Causes serious eye irritation
Repr. 2: H361d - Suspected of damaging the unborn child.
Skin Irrit. 2: H315 - Causes skin irritation
Skin Sens. 1: H317 - May cause an allergic skin reaction
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

Classification procedure:

Aquatic Chronic 3: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -