

## 06L - LIXIVIATING SELF-POLISHING ANTIFOULING Colours: 7903, 7905, 7906, 7949

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** 06L - LIXIVIATING SELF-POLISHING ANTIFOULING  
Colours: 7903, 7905, 7906, 7949

**Other means of identification:**

Non-applicable

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Antifouling paint

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

Industrias Titán, S.A.U.

Pol. Ind. Pratense, calle 114 nº 17-19

08820 El Prat de Llobregat - Barcelona - España

Phone.: +34 934 797 494 - Fax: +34 934 797 495

msds@titanlux.es

http://www.titanlux.es

**1.4 Emergency telephone number:** +34 934 797 494 (7:30-14:30 h.) (working hours)

### SECTION 2: HAZARDS IDENTIFICATION \*\*

**2.1 Classification of the substance or mixture:**

**CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute toxicity, Category 4, H312+H332

Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410

Eye Dam. 1: Serious eye damage, Category 1, H318

Flam. Liq. 3: Flammable liquids, Category 3, H226

Repr. 2: Reproductive toxicity, Category 2, H361

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT RE 2: Specific target organ toxicity if swallowed, repeated exposure, Category 2, H373

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

Danger



**Hazard statements:**

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H335 - May cause respiratory irritation.

**Precautionary statements:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

## 06L - LIXIVIATING SELF-POLISHING ANTIFOULING Colours: 7903, 7905, 7906, 7949

### SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)

P101: If medical advice is needed, have product container or label at hand.  
 P102: Keep out of reach of children.  
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P264: Wash thoroughly after handling.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.  
 P501: Dispose of contents/container according to the separated collection system used in your municipality.

#### Supplementary information:

Contains zinc ethylenebis(dithiocarbamate)(polymeric).  
 EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### Substances that contribute to the classification

Dicopper oxide; Xylene; Rosin; Hydrocarbons, C9, aromatics

UFI: F830-40H1-300W-YTQ0

#### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

\*\* Changes with regards to the previous version

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

**Chemical description:** Mixture composed of additives, aggregates, pigments and resins in solvents

#### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 1317-39-1 EC: 215-270-7 Index: 029-002-00-X REACH: 01-2119513794-36-XXXX	<b>Dicopper oxide<sup>(1)</sup></b> Regulation 1272/2008 Acute Tox. 4: H302+H332; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318 - Danger	ATP ATP09  20 - <25 %
CAS: 7727-43-7 EC: 231-784-4 Index: Non-applicable REACH: 01-2119491274-35-XXXX	<b>Barium Sulfate<sup>(2)</sup></b> Regulation 1272/2008	Not classified 20 - <25 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(1)</sup></b> Regulation 1272/2008 Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	Self-classified  15 - <20 %
CAS: 8050-09-7 EC: 232-475-7 Index: 650-015-00-7 REACH: 01-2119480418-32-XXXX	<b>Rosin<sup>(1)</sup></b> Regulation 1272/2008 Skin Sens. 1: H317 - Warning	ATP CLP00  7,5 - <10 %
CAS: 1314-13-2 EC: 215-222-5 Index: 030-013-00-7 REACH: 01-2119463881-32-XXXX	<b>zinc oxide<sup>(1)</sup></b> Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	ATP CLP00  5 - <7,5 %
CAS: 64742-95-6 EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35-XXXX	<b>Hydrocarbons, C9, aromatics<sup>(1)</sup></b> Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger	Self-classified  5 - <7,5 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>(2)</sup> Substance with a Union workplace exposure limit

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

## 06L - LIXIVIATING SELF-POLISHING ANTIFOULING Colours: 7903, 7905, 7906, 7949

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\* (continued)

Identification	Chemical name/Classification	Concentration
CAS: 1330-78-5 EC: 215-548-8 Index: Non-applicable REACH: 01-2119531335-46-XXXX	<b>Tris(methylphenyl) phosphate<sup>(1)</sup></b> Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Repr. 2: H361 - Warning	Self-classified <b>2,5 - &lt;5 %</b>
CAS: 12122-67-7 EC: 235-180-1 Index: Non-applicable REACH: Non-applicable	<b>zinc ethylenebis(dithiocarbamate)(polymeric)<sup>(1)</sup></b> Regulation 1272/2008 Aquatic Chronic 1: H410; Flam. Sol. 1: H228; Repr. 2: H361d; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	Self-classified <b>1,5 - &lt;2 %</b>
CAS: 13463-41-7 EC: 236-671-3 Index: 613-333-00-7 REACH: 01-2119511196-46-XXXX	<b>Pyrithione zinc<sup>(1)</sup></b> Regulation 1272/2008 Acute Tox. 2: H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Repr. 1B: H360D; STOT RE 1: H372 - Danger	ATP ATP15 <b>0,1 - &lt;0,2 %</b>

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

\*\* Changes with regards to the previous version

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

##### By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

##### By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

##### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

##### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media:

##### Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

##### Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

- CONTINUED ON NEXT PAGE -

**06L - LIXIVIATING SELF-POLISHING ANTIFOULING  
Colours: 7903, 7905, 7906, 7949****SECTION 5: FIREFIGHTING MEASURES (continued)**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling:****A.- Precautions for safe manipulation**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

**B.- Technical recommendations for the prevention of fires and explosions**

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

**C.- Technical recommendations to prevent ergonomic and toxicological risks**

**PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT.** Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

**D.- Technical recommendations to prevent environmental risks**

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:****A.- Technical measures for storage**

Minimum Temp.: 5 °C  
Maximum Temp.: 40 °C

- CONTINUED ON NEXT PAGE -

**06L - LIXIVIATING SELF-POLISHING ANTIFOULING**  
**Colours: 7903, 7905, 7906, 7949**

**SECTION 7: HANDLING AND STORAGE (continued)**

Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits		
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4		IOELV (8h)		0,5 mg/m <sup>3</sup>
		IOELV (STEL)		
Xylene CAS: 1330-20-7 EC: 215-535-7		IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
		IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dicopper oxide CAS: 1317-39-1 EC: 215-270-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	137 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	10 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
Rosin CAS: 8050-09-7 EC: 232-475-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,131 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	10 mg/m <sup>3</sup>
zinc oxide CAS: 1314-13-2 EC: 215-222-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	0,5 mg/m <sup>3</sup>
Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: 918-668-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	150 mg/m <sup>3</sup>	Non-applicable
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,41 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,18 mg/m <sup>3</sup>	Non-applicable
Pyrithione zinc CAS: 13463-41-7 EC: 236-671-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,01 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dicopper oxide CAS: 1317-39-1 EC: 215-270-7	Oral	0,082 mg/kg	Non-applicable	0,041 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable

- CONTINUED ON NEXT PAGE -

**06L - LIXIVIATING SELF-POLISHING ANTIFOULING**  
**Colours: 7903, 7905, 7906, 7949**
**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	Oral	Non-applicable	Non-applicable	13000 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	10 mg/m <sup>3</sup>	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>
Rosin CAS: 8050-09-7 EC: 232-475-7	Oral	Non-applicable	Non-applicable	1,065 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,065 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
zinc oxide CAS: 1314-13-2 EC: 215-222-5	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable
Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: 918-668-5	Oral	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	11 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	32 mg/m <sup>3</sup>	Non-applicable
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	Oral	Non-applicable	Non-applicable	0,02 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,15 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,03 mg/m <sup>3</sup>	Non-applicable

**PNEC:**

Identification					
Dicopper oxide CAS: 1317-39-1 EC: 215-270-7	STP	0,23 mg/L	Fresh water	0,0078 mg/L	
	Soil	65 mg/kg	Marine water	0,0052 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	87 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	676 mg/kg	
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	STP	62,2 mg/L	Fresh water	0,115 mg/L	
	Soil	207,7 mg/kg	Marine water	Non-applicable	
	Intermittent	Non-applicable	Sediment (Fresh water)	600,4 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable	
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L	
	Soil	2,31 mg/kg	Marine water	0,327 mg/L	
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg	
Rosin CAS: 8050-09-7 EC: 232-475-7	STP	1000 mg/L	Fresh water	0,002 mg/L	
	Soil	0 mg/kg	Marine water	0 mg/L	
	Intermittent	0,016 mg/L	Sediment (Fresh water)	0,007 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,001 mg/kg	
zinc oxide CAS: 1314-13-2 EC: 215-222-5	STP	0,1 mg/L	Fresh water	0,0206 mg/L	
	Soil	35,6 mg/kg	Marine water	0,0061 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	117,8 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	56,5 mg/kg	
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	STP	100 mg/L	Fresh water	0,001 mg/L	
	Soil	1,01 mg/kg	Marine water	0 mg/L	
	Intermittent	0,001 mg/L	Sediment (Fresh water)	2,05 mg/kg	
	Oral	0,00065 g/kg	Sediment (Marine water)	0,205 mg/kg	
Pyrrithione zinc CAS: 13463-41-7 EC: 236-671-3	STP	0,01 mg/L	Fresh water	0,00009 mg/L	
	Soil	1,02 mg/kg	Marine water	0,00009 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	0,009 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,009 mg/kg	

**8.2 Exposure controls:**

A.- General security and hygiene measures in the work place



- CONTINUED ON NEXT PAGE -

## 06L - LIXIVIATING SELF-POLISHING ANTIFOULING Colours: 7903, 7905, 7906, 7949



### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

#### B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

#### C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves		EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



#### D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

#### E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

#### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

#### Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

#### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	22,09 % weight
V.O.C. density at 20 °C:	398,36 kg/m <sup>3</sup> (398,36 g/L)
Average carbon number:	8,26

- CONTINUED ON NEXT PAGE -

**06L - LIXIVIATING SELF-POLISHING ANTIFOULING**  
**Colours: 7903, 7905, 7906, 7949**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Average molecular weight: 109,76 g/mol

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**
**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	According to the markings on the package
Odour:	Not available
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	143 °C
Vapour pressure at 20 °C:	648 Pa
Vapour pressure at 50 °C:	3609,27 Pa (3,61 kPa)
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	1600 - 1860 kg/m <sup>3</sup>
Relative density at 20 °C:	1,6 - 1,86
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *

**Flammability:**

Flash Point:	25 °C
Heat of combustion:	Non-applicable *
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	450 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

**Explosive:**

Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *

**9.2 Other information:**

Surface tension at 20 °C:	Non-applicable *
---------------------------	------------------

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**06L - LIXIVIATING SELF-POLISHING ANTIFOULING**  
**Colours: 7903, 7905, 7906, 7949**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Precaution	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION \*\***

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.  
IARC: Xylene (3); Hydrocarbons, C9, aromatics (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging fertility or the unborn child

\*\* Changes with regards to the previous version

**06L - LIXIVIATING SELF-POLISHING ANTIFOULING**  
**Colours: 7903, 7905, 7906, 7949**

**SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)**
**E- Sensitizing effects:**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

**F- Specific target organ toxicity (STOT) - single exposure:**

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	Route	Dose	
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	29 mg/L (4 h)	Rat
Rosin CAS: 8050-09-7 EC: 232-475-7	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
zinc oxide CAS: 1314-13-2 EC: 215-222-5	LD50 oral	7950 mg/kg	Mouse
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Dicopper oxide CAS: 1317-39-1 EC: 215-270-7	LD50 oral	1340 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	LD50 oral	15000 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	LD50 oral	15750 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Pyrithione zinc CAS: 13463-41-7 EC: 236-671-3	LD50 oral	221 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	0,14 mg/L (4 h)	Rat

\*\* Changes with regards to the previous version

**SECTION 12: ECOLOGICAL INFORMATION \*\***

The experimental information related to the eco-toxicological properties of the product itself is not available

Contains phosphates. Excessive discharge may cause eutrophication.

**12.1 Toxicity:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**06L - LIXIVIATING SELF-POLISHING ANTIFOULING**  
**Colours: 7903, 7905, 7906, 7949**

**SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)**

Identification	Acute toxicity		Species	Genus
Dicopper oxide CAS: 1317-39-1 EC: 215-270-7	LC50	0.8 mg/L (96 h)	Cyprinus carpio	Fish
	EC50	0.117 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Barium Sulfate CAS: 7727-43-7 EC: 231-784-4	LC50	76000 mg/L (96 h)	Salmo gairdneri	Fish
	EC50	Non-applicable		
	EC50	Non-applicable		
Rosin CAS: 8050-09-7 EC: 232-475-7	LC50	150 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	238 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	185 mg/L (72 h)	Selenastrum capricornutum	Algae
zinc oxide CAS: 1314-13-2 EC: 215-222-5	LC50	0.82 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50	3.4 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		
Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: 918-668-5	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	LC50	0.6 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	Non-applicable		
	EC50	Non-applicable		
zinc ethylenebis(dithiocarbamate)(polymeric) CAS: 12122-67-7 EC: 235-180-1	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
Pyrrithione zinc CAS: 13463-41-7 EC: 236-671-3	LC50	0.003 mg/L (96 h)	Pimephales promelas	Fish
	EC50	0.008 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		

**12.2 Persistence and degradability:**

Identification	Degradability		Biodegradability	
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
Rosin CAS: 8050-09-7 EC: 232-475-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	32 %
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	BOD5	Non-applicable	Concentration	2.6 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	22 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Other adverse effects:**

Not described

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

## 06L - LIXIVIATING SELF-POLISHING ANTIFOULING Colours: 7903, 7905, 7906, 7949

### SECTION 13: DISPOSAL CONSIDERATIONS

#### 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

#### Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

### SECTION 14: TRANSPORT INFORMATION

#### Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** III  
**14.5 Environmental hazards:** Yes  
**14.6 Special precautions for user**  
 Special regulations: 163, 367, 650  
 Tunnel restriction code: D/E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

#### Transport of dangerous goods by sea:

With regard to IMDG 39-18:



- 14.1 UN number:** UN1263  
**14.2 UN proper shipping name:** PAINT  
**14.3 Transport hazard class(es):** 3  
 Labels: 3  
**14.4 Packing group:** III  
**14.5 Marine pollutant:** Yes  
**14.6 Special precautions for user**  
 Special regulations: 223, 955, 163, 367  
 EmS Codes: F-E, S-E  
 Physico-Chemical properties: see section 9  
 Limited quantities: 5 L  
 Segregation group: Non-applicable  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

#### Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:

- CONTINUED ON NEXT PAGE -

## 06L - LIXIVIATING SELF-POLISHING ANTIFOULING Colours: 7903, 7905, 7906, 7949

### SECTION 14: TRANSPORT INFORMATION (continued)



<b>14.1 UN number:</b>	UN1263
<b>14.2 UN proper shipping name:</b>	PAINT
<b>14.3 Transport hazard class(es):</b>	3
Labels:	3
<b>14.4 Packing group:</b>	III
<b>14.5 Environmental hazards:</b>	Yes
<b>14.6 Special precautions for user</b>	
Physico-Chemical properties:	see section 9
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:</b>	Non-applicable

### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Composition of the active ingredients (Regulation (EU) No 528/2012): Dicopper oxide (20.9%); Pyrrithione zinc (0.1%)

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Dicopper oxide (Product-type 21) ; Pyrrithione zinc (Product-type 2, 6, 7, 9, 10, 21)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

#### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E1	ENVIRONMENTAL HAZARDS	100	200

#### Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- "whoopee" cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

- CONTINUED ON NEXT PAGE -

**06L - LIXIVIATING SELF-POLISHING ANTIFOULING  
Colours: 7903, 7905, 7906, 7949****SECTION 16: OTHER INFORMATION \*\*****Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

- New declared substances
  - Barium Sulfate (7727-43-7)
  - Hydrocarbons, C9, aromatics (64742-95-6)
- Removed substances
  - Ethylbenzene (100-41-4)
  - Xylene (1330-20-7)
  - Dipropylene Glycol Methyl Ether (34590-94-8)
  - 2-methoxy-1-methylethyl acetate (108-65-6)
  - Copper powder (7440-50-8)
  - Copper oxide (1317-38-0)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Hazard statements
- Supplementary information

**Texts of the legislative phrases mentioned in section 2:**

H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H335: May cause respiratory irritation.  
H373: May cause damage to organs through prolonged or repeated exposure (Oral).  
H317: May cause an allergic skin reaction.  
H400: Very toxic to aquatic life.  
H410: Very toxic to aquatic life with long lasting effects.  
H361: Suspected of damaging fertility or the unborn child.  
H312+H332: Harmful in contact with skin or if inhaled.  
H226: Flammable liquid and vapour.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 2: H330 - Fatal if inhaled.  
Acute Tox. 3: H301 - Toxic if swallowed.  
Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.  
Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.  
Aquatic Acute 1: H400 - Very toxic to aquatic life.  
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.  
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.  
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.  
Eye Dam. 1: H318 - Causes serious eye damage.  
Eye Irrit. 2: H319 - Causes serious eye irritation.  
Flam. Liq. 3: H226 - Flammable liquid and vapour.  
Flam. Sol. 1: H228 - Flammable solid.  
Repr. 1B: H360D - May damage the unborn child.  
Repr. 2: H361 - Suspected of damaging fertility or the unborn child.  
Repr. 2: H361d - Suspected of damaging the unborn child.  
Skin Irrit. 2: H315 - Causes skin irritation.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.  
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.  
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).  
STOT SE 3: H335 - May cause respiratory irritation.  
STOT SE 3: H336 - May cause drowsiness or dizziness.

**Classification procedure:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

**06L - LIXIVIATING SELF-POLISHING ANTIFOULING  
Colours: 7903, 7905, 7906, 7949****SECTION 16: OTHER INFORMATION \*\* (continued)**

Skin Irrit. 2: Calculation method  
Eye Dam. 1: Calculation method  
STOT SE 3: Calculation method  
STOT RE 2: Calculation method  
Skin Sens. 1: Calculation method  
Aquatic Acute 1: Calculation method  
Aquatic Chronic 1: Calculation method  
Repr. 2: Calculation method  
Acute Tox. 4: Calculation method  
Flam. Liq. 3: Calculation method (2.6.4.3)

**Advice related to training:**

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon

*\*\* Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -