

## 07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED Colours: 4401, 4403, 4404, 4405

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** 07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED  
Colours: 4401, 4403, 4404, 4405

**Other means of identification:**

Non-applicable

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Anti-scale paint

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

Industrias Titán, S.A.U.

Pol. Ind. Pratense, calle 114 nº 17-19

08820 El Prat de Llobregat - Barcelona - España

Phone: +34 934 797 494 - Fax: +34 934 797 495

msds@titanlux.es

http://www.titanlux.es

**1.4 Emergency telephone number:** +34 934 797 494 (7:30-14:30 h.) (working hours)

### SECTION 2: HAZARDS IDENTIFICATION \*\*

**2.1 Classification of the substance or mixture:**

**CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute toxicity, Category 4, H312+H332

Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410

Eye Dam. 1: Serious eye damage, Category 1, H318

Flam. Liq. 3: Flammable liquids, Category 3, H226

Repr. 2: Reproductive toxicity, Category 2, H361

Skin Irrit. 2: Skin irritation, Category 2, H315

Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Oral), H373

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

Danger



**Hazard statements:**

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H335 - May cause respiratory irritation.

**Precautionary statements:**

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

## 07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED Colours: 4401, 4403, 4404, 4405

### SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)

P101: If medical advice is needed, have product container or label at hand.  
 P102: Keep out of reach of children.  
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P264: Wash thoroughly after handling.  
 P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.  
 P501: Dispose of contents/container according to the separated collection system used in your municipality.

#### Supplementary information:

Contains Rosin, zinc ethylenebis(dithiocarbamate)(polymeric).  
 EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

\*\* Changes with regards to the previous version

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

**Chemical description:** Mixture composed of additives, aggregates, pigments and resins in solvents

#### Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:


Identification	Chemical name/Classification	Concentration
CAS: 1317-39-1 EC: 215-270-7 Index: 029-002-00-X REACH: 01-2119513794-36-XXXX	<b>Dicopper oxide<sup>(1)</sup></b> Regulation 1272/2008 Acute Tox. 4: H302+H332; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318 - Danger	ATP ATP17  25 - <50 %
CAS: 1330-20-7 EC: 215-535-7 Index: 601-022-00-9 REACH: 01-2119488216-32-XXXX	<b>Xylene<sup>(1)</sup></b> Regulation 1272/2008 Acute Tox. 4: H312+H332; Aquatic Chronic 3: H412; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger	Self-classified  15 - <20 %
CAS: 8050-09-7 EC: 232-475-7 Index: 650-015-00-7 REACH: 01-2119480418-32-XXXX	<b>Rosin<sup>(1)</sup></b> Regulation 1272/2008 Skin Sens. 1: H317 - Warning	ATP CLP00  10 - <12,5 %
CAS: 1314-13-2 EC: 215-222-5 Index: 030-013-00-7 REACH: 01-2119463881-32-XXXX	<b>zinc oxide<sup>(1)</sup></b> Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	ATP CLP00  7,5 - <10 %
CAS: 1330-78-5 EC: 215-548-8 Index: Non-applicable REACH: 01-2119531335-46-XXXX	<b>Tris(methylphenyl) phosphate<sup>(1)</sup></b> Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Repr. 2: H361 - Warning	Self-classified  2,5 - <5 %
CAS: 12122-67-7 EC: 235-180-1 Index: Non-applicable REACH: Non-applicable	<b>zinc ethylenebis(dithiocarbamate)(polymeric)<sup>(1)</sup></b> Regulation 1272/2008 Aquatic Chronic 1: H410; Flam. Sol. 1: H228; Repr. 2: H361d; Skin Sens. 1: H317; STOT SE 3: H335 - Danger	Self-classified  2,5 - <5 %
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	<b>2-methoxy-1-methylethyl acetate<sup>(2)</sup></b> Regulation 1272/2008 Flam. Liq. 3: H226 - Warning	ATP ATP01  2,5 - <5 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>(2)</sup> Substance with a Union workplace exposure limit

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED**  
**Colours: 4401, 4403, 4404, 4405**

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)**

Identification	Chemical name/Classification	Concentration
CAS: 13463-41-7 EC: 236-671-3 Index: 613-333-00-7 REACH: 01-2119511196-46-XXXX	<b>Pyrithione zinc<sup>(1)</sup></b>  Regulation 1272/2008  Acute Tox. 2: H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Repr. 1B: H360D; STOT RE 1: H372 - Danger	ATP ATP15    <b>0,05 - &lt;0,1 %</b>

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>(2)</sup> Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST AID MEASURES**
**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

**SECTION 5: FIREFIGHTING MEASURES**
**5.1 Extinguishing media:**
**Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>).

**Unsuitable extinguishing media:**

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

- CONTINUED ON NEXT PAGE -

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED  
Colours: 4401, 4403, 4404, 4405****SECTION 5: FIREFIGHTING MEASURES (continued)**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**For emergency responders:**

See section 8.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling:****A.- General precautions for safe use**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

**B.- Technical recommendations for the prevention of fires and explosions**

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

**C.- Technical recommendations on general occupational hygiene**

**PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT.** Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

**D.- Technical recommendations to prevent environmental risks**

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:****A.- Technical measures for storage**

Minimum Temp.:	5 °C
Maximum Temp.:	40 °C

- CONTINUED ON NEXT PAGE -

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED**  
**Colours: 4401, 4403, 4404, 4405**

**SECTION 7: HANDLING AND STORAGE (continued)**

Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
	IOELV (8h)	50 ppm	221 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	IOELV (STEL)	100 ppm	442 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	IOELV (8h)	50 ppm	275 mg/m <sup>3</sup>
	IOELV (STEL)	100 ppm	550 mg/m <sup>3</sup>

**DNEL (Workers):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dicopper oxide CAS: 1317-39-1 EC: 215-270-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	137 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	1 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	212 mg/kg	Non-applicable
	Inhalation	442 mg/m <sup>3</sup>	442 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>	221 mg/m <sup>3</sup>
Rosin CAS: 8050-09-7 EC: 232-475-7	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	2,131 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	10 mg/m <sup>3</sup>
zinc oxide CAS: 1314-13-2 EC: 215-222-5	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	5 mg/m <sup>3</sup>	0,5 mg/m <sup>3</sup>
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,41 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,18 mg/m <sup>3</sup>	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	796 mg/kg	Non-applicable
	Inhalation	Non-applicable	550 mg/m <sup>3</sup>	275 mg/m <sup>3</sup>	Non-applicable
Pyrrithione zinc CAS: 13463-41-7 EC: 236-671-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,01 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable

**DNEL (General population):**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dicopper oxide CAS: 1317-39-1 EC: 215-270-7	Oral	0,082 mg/kg	Non-applicable	0,041 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
Xylene CAS: 1330-20-7 EC: 215-535-7	Oral	Non-applicable	Non-applicable	12,5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	125 mg/kg	Non-applicable
	Inhalation	260 mg/m <sup>3</sup>	260 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>	65,3 mg/m <sup>3</sup>

- CONTINUED ON NEXT PAGE -

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED**  
**Colours: 4401, 4403, 4404, 4405**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Rosin CAS: 8050-09-7 EC: 232-475-7	Oral	Non-applicable	Non-applicable	1,065 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1,065 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable
zinc oxide CAS: 1314-13-2 EC: 215-222-5	Oral	Non-applicable	Non-applicable	0,83 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	83 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	2,5 mg/m <sup>3</sup>	Non-applicable
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	Oral	Non-applicable	Non-applicable	0,02 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,15 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,03 mg/m <sup>3</sup>	Non-applicable
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	320 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	33 mg/m <sup>3</sup>	33 mg/m <sup>3</sup>

**PNEC:**

Identification					
Dicopper oxide CAS: 1317-39-1 EC: 215-270-7	STP	0,23 mg/L	Fresh water	0,0078 mg/L	
	Soil	65 mg/kg	Marine water	0,0052 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	87 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	676 mg/kg	
Xylene CAS: 1330-20-7 EC: 215-535-7	STP	6,58 mg/L	Fresh water	0,327 mg/L	
	Soil	2,31 mg/kg	Marine water	0,327 mg/L	
	Intermittent	0,327 mg/L	Sediment (Fresh water)	12,46 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	12,46 mg/kg	
Rosin CAS: 8050-09-7 EC: 232-475-7	STP	1000 mg/L	Fresh water	0,002 mg/L	
	Soil	0 mg/kg	Marine water	0 mg/L	
	Intermittent	0,016 mg/L	Sediment (Fresh water)	0,007 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,001 mg/kg	
zinc oxide CAS: 1314-13-2 EC: 215-222-5	STP	0,1 mg/L	Fresh water	0,0206 mg/L	
	Soil	35,6 mg/kg	Marine water	0,0061 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	117,8 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	56,5 mg/kg	
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	STP	100 mg/L	Fresh water	0,001 mg/L	
	Soil	1,01 mg/kg	Marine water	0 mg/L	
	Intermittent	0,001 mg/L	Sediment (Fresh water)	2,05 mg/kg	
	Oral	0,00065 g/kg	Sediment (Marine water)	0,205 mg/kg	
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	STP	100 mg/L	Fresh water	0,635 mg/L	
	Soil	0,29 mg/kg	Marine water	0,064 mg/L	
	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,329 mg/kg	
Pyrrithione zinc CAS: 13463-41-7 EC: 236-671-3	STP	0,01 mg/L	Fresh water	0,00009 mg/L	
	Soil	1,02 mg/kg	Marine water	0,00009 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	0,009 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,009 mg/kg	

**8.2 Exposure controls:**

**A.- Individual protection measures, such as personal protective equipment**



As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**



- CONTINUED ON NEXT PAGE -

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED**  
**Colours: 4401, 4403, 4404, 4405**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles		EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)		EN 420:2004+A1:2010	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	19,91 % weight
V.O.C. density at 20 °C:	378,36 kg/m <sup>3</sup> (378,36 g/L)
Average carbon number:	7,71
Average molecular weight:	109,89 g/mol

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED**  
**Colours: 4401, 4403, 4404, 4405**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:	Liquid
Appearance:	Viscous
Colour:	Not available
Odour:	Characteristic
Odour threshold:	Non-applicable *

**Volatility:**

Boiling point at atmospheric pressure:	138 °C
Vapour pressure at 20 °C:	717 Pa
Vapour pressure at 50 °C:	3990,48 Pa (3,99 kPa)
Evaporation rate at 20 °C:	Non-applicable *

**Product description:**

Density at 20 °C:	1600 - 2200 kg/m <sup>3</sup>
Relative density at 20 °C:	1,6 - 2,2
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20,5 mm <sup>2</sup> /s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

**Flammability:**

Flash Point:	25 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	300 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available

**Particle characteristics:**

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

**9.2 Other information:**

**Information with regard to physical hazard classes:**

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

**Other safety characteristics:**

Surface tension at 20 °C:	Non-applicable *
---------------------------	------------------

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED**  
**Colours: 4401, 4403, 4404, 4405**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the indicated conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Precaution	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Incompatible materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.  
IARC: Diiron trioxide (3); Xylene (3); Poly(tetrafluoroethylene) (3); Talc (3); Titanium dioxide (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging fertility or the unborn child

E- Sensitizing effects:

- CONTINUED ON NEXT PAGE -

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED**  
**Colours: 4401, 4403, 4404, 4405**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

**F- Specific target organ toxicity (STOT) - single exposure:**

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

**G- Specific target organ toxicity (STOT)-repeated exposure:**

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

**H- Aspiration hazard:**

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	Route	Toxicity	
Xylene CAS: 1330-20-7 EC: 215-535-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	29 mg/L (4 h)	Rat
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LD50 oral	8532 mg/kg	Rat
	LD50 dermal	5100 mg/kg	Rat
	LC50 inhalation	30 mg/L (4 h)	Rat
Rosin CAS: 8050-09-7 EC: 232-475-7	LD50 oral	4100 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Dicopper oxide CAS: 1317-39-1 EC: 215-270-7	LD50 oral	500 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	11 mg/L (ATEi)	
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	LD50 oral	15750 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
zinc oxide CAS: 1314-13-2 EC: 215-222-5	LD50 oral	7950 mg/kg	Mouse
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
Pyrrithione zinc CAS: 13463-41-7 EC: 236-671-3	LD50 oral	221 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	0,14 mg/L (4 h)	Rat

- CONTINUED ON NEXT PAGE -

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED**  
**Colours: 4401, 4403, 4404, 4405**

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

Contains phosphates. Excessive discharge may cause eutrophication.

**12.1 Toxicity:**
**Acute toxicity:**

Identification	Concentration	Species	Genus
Dicopper oxide CAS: 1317-39-1 EC: 215-270-7	LC50 0,8 mg/L (96 h)	Cyprinus carpio	Fish
	EC50 0,117 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 Non-applicable		
Xylene CAS: 1330-20-7 EC: 215-535-7	LC50 >10 - 100 (96 h)		Fish
	EC50 >10 - 100 (48 h)		Crustacean
	EC50 >10 - 100 (72 h)		Algae
Rosin CAS: 8050-09-7 EC: 232-475-7	LC50 150 mg/L (96 h)	Brachydanio rerio	Fish
	EC50 238 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 185 mg/L (72 h)	Selenastrum capricornutum	Algae
zinc oxide CAS: 1314-13-2 EC: 215-222-5	LC50 0,82 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50 3,4 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 Non-applicable		
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	LC50 0,6 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50 Non-applicable		
	EC50 Non-applicable		
zinc ethylenebis(dithiocarbamate)(polymeric) CAS: 12122-67-7 EC: 235-180-1	LC50 >0.1 - 1 (96 h)		Fish
	EC50 >0.1 - 1 (48 h)		Crustacean
	EC50 >0.1 - 1 (72 h)		Algae
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	LC50 161 mg/L (96 h)	Pimephales promelas	Fish
	EC50 481 mg/L (48 h)	Daphnia sp.	Crustacean
	EC50 Non-applicable		
Pyrithione zinc CAS: 13463-41-7 EC: 236-671-3	LC50 0,003 mg/L (96 h)	Pimephales promelas	Fish
	EC50 0,008 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 Non-applicable		

**Chronic toxicity:**

Identification	Concentration	Species	Genus
Xylene CAS: 1330-20-7 EC: 215-535-7	NOEC 1,3 mg/L	Oncorhynchus mykiss	Fish
	NOEC 1,17 mg/L	Ceriodaphnia dubia	Crustacean
zinc oxide CAS: 1314-13-2 EC: 215-222-5	NOEC 0,44 mg/L	Oncorhynchus mykiss	Fish
	NOEC 0,031 mg/L	Daphnia magna	Crustacean

- CONTINUED ON NEXT PAGE -

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED**  
**Colours: 4401, 4403, 4404, 4405**
**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Concentration		Species	Genus
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	NOEC	0,01 mg/L	Jordanella floridae	Fish
	NOEC	0,1 mg/L	Daphnia magna	Crustacean
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	NOEC	47,5 mg/L	Oryzias latipes	Fish
	NOEC	100 mg/L	Daphnia magna	Crustacean
Pyrethione zinc CAS: 13463-41-7 EC: 236-671-3	NOEC	Non-applicable		
	NOEC	0,022 mg/L	Daphnia magna	Crustacean

**12.2 Persistence and degradability:**

Identification	Degradability		Biodegradability	
Xylene CAS: 1330-20-7 EC: 215-535-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
Rosin CAS: 8050-09-7 EC: 232-475-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	32 %
Tris(methylphenyl) phosphate CAS: 1330-78-5 EC: 215-548-8	BOD5	Non-applicable	Concentration	2.6 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	22 %
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BOD5	Non-applicable	Concentration	785 mg/L
	COD	Non-applicable	Period	8 days
	BOD5/COD	Non-applicable	% Biodegradable	100 %

**12.3 Bioaccumulative potential:**

Identification	Bioaccumulation potential	
Xylene CAS: 1330-20-7 EC: 215-535-7	BCF	9
	Pow Log	2.77
	Potential	Low
2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9	BCF	1
	Pow Log	0.43
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Xylene CAS: 1330-20-7 EC: 215-535-7	Koc	202	Henry	524,86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED**  
**Colours: 4401, 4403, 4404, 4405**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

**Type of waste (Regulation (EU) No 1357/2014):**

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP10 Toxic for reproduction, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2021 and RID 2021:



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
- Labels:** 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**
  - Special regulations: 163, 367, 650
  - Tunnel restriction code: D/E
  - Physico-Chemical properties: see section 9
  - Limited quantities: 5 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 39-18:

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED  
Colours: 4401, 4403, 4404, 4405**

**SECTION 14: TRANSPORT INFORMATION (continued)**



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** Yes
- 14.6 Special precautions for user**  
Special regulations: 223, 955, 163, 367  
EmS Codes: F-E, S-E  
Physico-Chemical properties: see section 9  
Limited quantities: 5 L  
Segregation group: Non-applicable
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2022:



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3  
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** Yes
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Composition of the active ingredients (Regulation (EU) No 528/2012): Dicopper oxide (37.983%); Pyrithione zinc (0.1%)

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Dicopper oxide (Product-type 21) ; Pyrithione zinc (Product-type 2, 6, 7, 9, 10, 21)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

**Seveso III:**

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E1	ENVIRONMENTAL HAZARDS	100	200

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

- CONTINUED ON NEXT PAGE -

**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED  
Colours: 4401, 4403, 4404, 4405****SECTION 15: REGULATORY INFORMATION (continued)**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION \*\*****Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Hazard statements
- Supplementary information

**Texts of the legislative phrases mentioned in section 2:**

H315: Causes skin irritation.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

H410: Very toxic to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure (Oral).

H317: May cause an allergic skin reaction.

H400: Very toxic to aquatic life.

H361: Suspected of damaging fertility or the unborn child.

H226: Flammable liquid and vapour.

H312+H332: Harmful in contact with skin or if inhaled.

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled.

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Flam. Sol. 1: H228 - Flammable solid.

Repr. 1B: H360D - May damage the unborn child.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

STOT SE 3: H335 - May cause respiratory irritation.

**Advice related to training:**

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -



**07M - UNIV. SELF-POLISHING ANTIFOULING MEDIUM SPEED  
Colours: 4401, 4403, 4404, 4405****SECTION 16: OTHER INFORMATION \*\* (continued)****Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

*\*\* Changes with regards to the previous version*

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -