# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

#### **H41 - MOULD REMOVER H41**

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: H41 - MOULD REMOVER H41

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Cleaner

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Industrias Titán, S.A.U.

Pol. Ind. Pratense, calle 114 no 17-19

08820 El Prat de Llobregat - Barcelona - España Phone.: +34 934 797 494 - Fax: +34 934 797 495

msds@titanlux.es http://www.titanlux.es

**1.4 Emergency telephone number:** +34 934 797 494 (7:30-14:30 h.) (working hours)

# SECTION 2: HAZARDS IDENTIFICATION \*\*

#### 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Acute 1: Hazardous to the aquatic environment, acute hazard, Category 1, H400 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Dam. 1: Serious eye damage, Category 1, H318

Skin Irrit. 2: Skin irritation, Category 2, H315

#### 2.2 Label elements:

## CLP Regulation (EC) No 1272/2008:

#### Danger





#### **Hazard statements:**

Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects

Eye Dam. 1: H318 - Causes serious eye damage Skin Irrit. 2: H315 - Causes skin irritation

#### **Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand

P264: Wash thoroughly after handling

P280: Wear protective gloves/protective clothing/eye protection/face protection

P302+P352: IF ON SKIN: Wash with plenty of water

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing

P310: Immediately call a poison center/doctor

P501: Dispose of contents/container according to the separated collection system used in your municipality

#### Supplementary information:

EUH208: Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction

## Substances that contribute to the classification

Didecyldimethylammonium chloride

# 2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Date of compilation: 09/08/2012 Revised: 18/02/2020 Version: 5 (Replaced 4) Page 1/12

<sup>\*\*</sup> Changes with regards to the previous version

<sup>\*\*</sup> Changes with regards to the previous version

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

#### **H41 - MOULD REMOVER H41**

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Aqueous mixture composed of additives

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		
CAS:	7173-51-5	Didecyldimethylamm	onium chloride <sup>(1)</sup>	ATP CLP00	
EC: 230-525-2 Index: 612-131-00-6 REACH: 01-2119945987-15- XXXX	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Skin Corr. 1B: H314 - Danger	(1) (2) ( <u>1</u> )	2,5 - <5 %	
CAS:	67-63-0	Propan-2-ol <sup>(1)</sup>		ATP CLP00	
Index:		Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	<b>(!)</b>	1,5 - <2 %
CAS:	2634-33-5	1,2-benzisothiazol-3	(2H)-one <sup>(1)</sup>	ATP CLP00	
Index:	EC: 220-120-9	Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger	(1) (2) (1)	0,01 - <0,02 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

# **SECTION 4: FIRST AID MEASURES**

#### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

#### By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

# By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

# By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

## By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

# 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

# **SECTION 5: FIREFIGHTING MEASURES**

## 5.1 Extinguishing media:

Date of compilation: 09/08/2012 Revised: 18/02/2020 Version: 5 (Replaced 4) **Page 2/12** 

<sup>\*\*</sup> Changes with regards to the previous version

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

### H41 - MOULD REMOVER H41

# SECTION 5: FIREFIGHTING MEASURES (continued)

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use full jet water as an extinguishing agent.

### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

## 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

#### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

# 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

# 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

# **SECTION 7: HANDLING AND STORAGE**

### 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

# 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage



### H41 - MOULD REMOVER H41

# SECTION 7: HANDLING AND STORAGE (continued)

5 °C Minimum Temp.: 40 °C Maximum Temp.: Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

#### Specific end use(s): 7.3

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 **Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace There are no occupational exposure limits for the substances contained in the product

### **DNEL (Workers):**

		Short e	exposure Long exposure		xposure
Identification		Systemic	Local	Systemic	Local
Didecyldimethylammonium chloride	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 7173-51-5	Dermal	Non-applicable	Non-applicable	8,6 mg/kg	Non-applicable
EC: 230-525-2	Inhalation	Non-applicable	Non-applicable	18,2 mg/m <sup>3</sup>	Non-applicable
Propan-2-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 67-63-0	Dermal	Non-applicable	Non-applicable	888 mg/kg	Non-applicable
EC: 200-661-7	Inhalation	Non-applicable	Non-applicable	500 mg/m <sup>3</sup>	Non-applicable

# **DNEL (General population):**

		Short e	exposure Long exposure		xposure
Identification		Systemic	Local	Systemic	Local
Propan-2-ol	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable
CAS: 67-63-0	Dermal	Non-applicable	Non-applicable	319 mg/kg	Non-applicable
EC: 200-661-7	Inhalation	Non-applicable	Non-applicable	89 mg/m <sup>3</sup>	Non-applicable

#### PNEC:

Identification				
Didecyldimethylammonium chloride	STP	0,595 mg/L	Fresh water	0,002 mg/L
CAS: 7173-51-5	Soil	1,4 mg/kg	Marine water	0,0002 mg/L
EC: 230-525-2	Intermittent	0,00029 mg/L	Sediment (Fresh water)	2,82 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,28 mg/kg
Propan-2-ol	STP	2251 mg/L	Fresh water	140,9 mg/L
CAS: 67-63-0	Soil	28 mg/kg	Marine water	140,9 mg/L
EC: 200-661-7	Intermittent	140,9 mg/L	Sediment (Fresh water)	552 mg/kg
	Oral	0,16 g/kg	Sediment (Marine water)	552 mg/kg

#### 8.2 **Exposure controls:**

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

# **H41 - MOULD REMOVER H41**

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374.

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

# D.- Ocular and facial protection

ı	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2001 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

## E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CATII	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

# F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
<b>*</b>	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<b>O</b> +	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

## **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

## Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 1,61 % weight

V.O.C. density at 20 °C: 16,38 kg/m³ (16,38 g/L)

Average carbon number: 3

Average molecular weight: 60,31 g/mol

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Colour:

Colour:

Characteristic

 ${}^*\mathrm{Not}$  relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 09/08/2012 Revised: 18/02/2020 Version: 5 (Replaced 4) **Page 5/12** 

# H41 - MOULD REMOVER H41

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Odour threshold: Non-applicable \*

Volatility:

TITAN

Boiling point at atmospheric pressure: 100 °C Vapour pressure at 20 °C: 2364 Pa

Vapour pressure at 50 °C: 12447,83 Pa (12,45 kPa)

Evaporation rate at 20 °C: Non-applicable \*

**Product description:** 

Density at 20 °C: 990 - 1050 kg/m<sup>3</sup> Relative density at 20 °C: 0,992 - 1,052 Dynamic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 20 °C: Non-applicable \* Kinematic viscosity at 40 °C: Non-applicable \* Concentration: Non-applicable \* pH: Non-applicable \* Vapour density at 20 °C: Non-applicable \* Partition coefficient n-octanol/water 20 °C: Non-applicable \* Solubility in water at 20 °C: Non-applicable \* Solubility properties: Non-applicable \* Decomposition temperature: Non-applicable \* Melting point/freezing point: Non-applicable \* Explosive properties: Non-applicable \*

Flammability:

Oxidising properties:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas): Non-applicable \*

Autoignition temperature: 399 °C

Lower flammability limit: Non-applicable \*
Upper flammability limit: Non-applicable \*

Explosive:

Lower explosive limit: Non-applicable \*
Upper explosive limit: Non-applicable \*

9.2 Other information:

Surface tension at 20 °C:

Refraction index:

Non-applicable \*

Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

# 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

Non-applicable \*

#### 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

# 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Date of compilation: 09/08/2012 Revised: 18/02/2020 Version: 5 (Replaced 4) Page 6/12



# H41 - MOULD REMOVER H41

# SECTION 10: STABILITY AND REACTIVITY (continued)

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

#### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION \*\*

## 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

### **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Produces skin inflammation.
  - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

    IARC: Propan-2-ol (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Date of compilation: 09/08/2012 Revised: 18/02/2020 Version: 5 (Replaced 4) Page 7/12

<sup>\*\*</sup> Changes with regards to the previous version



# **H41 - MOULD REMOVER H41**

# SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

### Other information:

Non-applicable

### Specific toxicology information on the substances:

Identification	Acut	e toxicity	Genus
Propan-2-ol	LD50 oral	5280 mg/kg	Rat
CAS: 67-63-0	LD50 dermal	12800 mg/kg	Rat
EC: 200-661-7	LC50 inhalation	72,6 mg/L (4 h)	Rat
Didecyldimethylammonium chloride	LD50 oral	500 mg/kg	Rat
CAS: 7173-51-5	LD50 dermal	Non-applicable	
EC: 230-525-2	LC50 inhalation	Non-applicable	
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	Non-applicable	
EC: 220-120-9	LC50 inhalation	Non-applicable	

<sup>\*\*</sup> Changes with regards to the previous version

# SECTION 12: ECOLOGICAL INFORMATION \*\*

The experimental information related to the eco-toxicological properties of the product itself is not available

# 12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
Didecyldimethylammonium chloride	LC50	0.33 mg/L (96 h)	Pimephales promelas	Fish
CAS: 7173-51-5	EC50	0.06 mg/L (48 h)	Daphnia magna	Crustacean
EC: 230-525-2	EC50	Non-applicable		
Propan-2-ol	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
CAS: 67-63-0	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-661-7	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
1,2-benzisothiazol-3(2H)-one	LC50	0.1 - 1 mg/L (96 h)		Fish
CAS: 2634-33-5	EC50	0.1 - 1 mg/L		Crustacean
EC: 220-120-9	EC50	0.1 - 1 mg/L		Algae

# 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Didecyldimethylammonium chloride	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 7173-51-5	COD	Non-applicable	Period	28 days
EC: 230-525-2	BOD5/COD	Non-applicable	% Biodegradable	80 %
Propan-2-ol	BOD5	1.19 g O2/g	Concentration	100 mg/L
CAS: 67-63-0	COD	2.23 g O2/g	Period	14 days
EC: 200-661-7	BOD5/COD	0.53	% Biodegradable	86 %
1,2-benzisothiazol-3(2H)-one	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 2634-33-5	COD	Non-applicable	Period	28 days
EC: 220-120-9	BOD5/COD	Non-applicable	% Biodegradable	0 %

# 12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Didecyldimethylammonium chloride	BCF	81
CAS: 7173-51-5	Pow Log	4.66
EC: 230-525-2	Potential	Moderate
Propan-2-ol	BCF	3
CAS: 67-63-0	Pow Log	0.05
EC: 200-661-7	Potential	Low

<sup>\*\*</sup> Changes with regards to the previous version

Date of compilation: 09/08/2012 Revised: 18/02/2020 Version: 5 (Replaced 4) **Page 8/12** 



# **H41 - MOULD REMOVER H41**

# SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

Identification	Bioaccumulation potential		
1,2-benzisothiazol-3(2H)-one	BCF	2	
CAS: 2634-33-5	Pow Log	1.45	
EC: 220-120-9	Potential	Low	

#### 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Didecyldimethylammonium chloride	Koc	440000	Henry	Non-applicable
CAS: 7173-51-5	Conclusion	Immobile	Dry soil	Non-applicable
EC: 230-525-2	Surface tension	Non-applicable	Moist soil	Non-applicable
Propan-2-ol	Koc	1.5	Henry	8,207E-1 Pa·m³/mol
CAS: 67-63-0	Conclusion	Very High	Dry soil	Yes
EC: 200-661-7	Surface tension	2,24E-2 N/m (25 °C)	Moist soil	Yes

#### 12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

#### 12.6 Other adverse effects:

Not described

# **SECTION 13: DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods:

Code Description		Waste class (Regulation (EU) No 1357/2014)	
20 01 29*	detergents containing hazardous substances	Dangerous	

# Type of waste (Regulation (EU) No 1357/2014):

**HP14 Ecotoxic** 

# Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

# **Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# **SECTION 14: TRANSPORT INFORMATION**

#### Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:

- CONTINUED ON NEXT PAGE 
Date of compilation: 09/08/2012 Revised: 18/02/2020 Version: 5 (Replaced 4) Page 9/12

<sup>\*\*</sup> Changes with regards to the previous version

## Safety data sheet





### H41 - MOULD REMOVER H41

# SECTION 14: TRANSPORT INFORMATION (continued)

**14.1 UN number:** UN3082

**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2-

benzisothiazol-3(2H)-one; Didecyldimethylammonium chloride)

**14.3** Transport hazard class(es): 9

Labels:

14.4 Packing group: III14.5 Environmental hazards: Yes

14.6 Special precautions for user

Special regulations: 274, 335, 375, 601
Tunnel restriction code: Non-applicable
Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:

Non-applicable

#### Transport of dangerous goods by sea:

With regard to IMDG 38-16:

**14.1 UN number:** UN3082

**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2-

benzisothiazol-3(2H)-one; Didecyldimethylammonium chloride)

**14.3 Transport hazard class(es):** 9 Labels: 9

14.4 Packing group: III14.5 Environmental hazards: Yes

14.6 Special precautions for user

Special regulations: 335, 969, 274
EmS Codes: F-A, S-F
Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Non-applicable **Transport in bulk according** Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:

# Transport of dangerous goods by air:

With regard to IATA/ICAO 2019:



**14.1 UN number:** UN3082

**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2-benzisothiazol-3(2H)-one; Didecyldimethylammonium chloride)

**14.3** Transport hazard class(es): 9

Labels: 9
14.4 Packing group: III
14.5 Environmental hazards: Yes

14.6 Special precautions for user

Physico-Chemical properties: see section 9 **14.7 Transport in bulk according** Non-applicable

to Annex II of Marpol and

the IBC Code:

# **SECTION 15: REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Didecyldimethylammonium chloride, Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione, 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Date of compilation: 09/08/2012 Revised: 18/02/2020 Version: 5 (Replaced 4) Page 10/12

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

#### **H41 - MOULD REMOVER H41**

# SECTION 15: REGULATORY INFORMATION (continued)

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Didecyldimethylammonium chloride (Product-type 1, 2, 3, 4, 6, 8, 10, 11, 12); Propan-2-ol (Product-type 1, 2, 4); 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 10, 11, 12, 13); Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione (Product-type 2, 6, 11, 12, 13); 2-methyl-2H-isothiazol-3-one (Product-type 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Contains Didecyldimethylammonium chloride

#### Regulation (EC) No 648/2004 on detergents:

In accordance with this regulation the product complies with the following:

The tensoactives contained in this mixture comply with the biodegradibility criteria stipulated in Regulation (EC)  $n^0648/2004$  on detergents. The information to prove this is available to the relevant authorities of the Member States and will be shown to them by direct request or the request of a detergent manufacturer.

## Labelling for contents:

Preservation agents: 1,2-benzisothiazol-3(2H)-one (BENZISOTHIAZOLINONE), 2-methyl-2H-isothiazol-3-one (METHYLISOTHIAZOLINONE), Didecyldimethylammonium chloride (DIDECYLDIMONIUM CHLORIDE), Tetrahydro-1,3,4,6-tetrakis (hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione (TETRAMETHYLOLGLYCOLURIL).

#### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
E1		100	200

# Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Non-applicable

#### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

# Other legislation:

The product could be affected by sectorial legislation

- Regulation (EC) No 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products
- Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents
- Commission Regulation (EC) No 907/2006 of 20 June 2006 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes III and VII
- Commission Regulation (EC) No 551/2009 of 25 June 2009 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes V and VI thereto (surfactant derogation)

## 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

# **SECTION 16: OTHER INFORMATION**

### Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

· New declared substances

1,2-benzisothiazol-3(2H)-one (2634-33-5)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

· Precautionary statements

#### Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation

H318: Causes serious eye damage

H400: Very toxic to aquatic life

H411: Toxic to aquatic life with long lasting effects

Texts of the legislative phrases mentioned in section 3:

Date of compilation: 09/08/2012 Revised: 18/02/2020 Version: 5 (Replaced 4) Page 11/12

# Safety data sheet According to 1907/2006/EC (REACH), 2015/830/EU

#### **H41 - MOULD REMOVER H41**

# SECTION 16: OTHER INFORMATION (continued)

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects

Eye Dam. 1: H318 - Causes serious eye damage Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1: H317 - May cause an allergic skin reaction STOT SE 3: H336 - May cause drowsiness or dizziness

## Classification procedure:

Skin Irrit. 2: Calculation method Eye Dam. 1: Calculation method Aquatic Acute 1: Calculation method Aquatic Chronic 2: Calculation method

#### Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET 
Date of compilation: 09/08/2012 Revised: 18/02/2020 Version: 5 (Replaced 4) Page 12/12