


M32 - LASUR SYNTHETIC PROTECTOR MATT

Colours: 3800, 3801, 3802, 3803, 3806, 3809

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809
- Other means of identification:**
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Glaze
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Industrias Titán, S.A.U.
Pol. Ind. Pratense, calle 114 nº 17-19
08820 El Prat de Llobregat - Barcelona - España
Phone.: +34 934 797 494 - Fax: +34 934 797 495
msds@titanlux.es
http://www.titanlux.es
- 1.4 Emergency telephone number:** Toxicological information service:
Instituto Nacional de Toxicología y Ciencias Forenses (INTCF)
Tel: +34 91 562 04 20 (24 h - 7/7 days)

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
- CLP Regulation (EC) No 1272/2008:**
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Flam. Liq. 3: Flammable liquids, Category 3, H226
Skin Sens. 1A: Sensitisation, skin, Category 1A, H317
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
- CLP Regulation (EC) No 1272/2008:**
- Warning**
- 
- Hazard statements:**
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P370+P378: In case of fire: Use ABC powder extinguisher to extinguish.
P501: Dispose of contents/container according to the separated collection system used in your municipality.
- Supplementary information:**
EUH066: Repeated exposure may cause skin dryness or cracking.
Contains 3-iodo-2-propynyl Butylcarbamate.
- Substances that contribute to the classification**
Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics; Hydrocarbons, C9, aromatics; Reaction mass of bis (1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

UFI: DGA0-N0GC-U00G-HGNE

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS **

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | Concentration |
|---|---|---------------------------------|
| CAS: 64742-48-9 EC: 919-857-5 Index: Non-applicable REACH: 01-2119463258-33-XXXX | Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics⁽¹⁾ Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Danger | Self-classified 25 - <50 % |
| CAS: 112945-52-5 EC: Non-applicable Index: Non-applicable REACH: 01-2119379499-16-XXXX | Synthetic Silicon Dioxide⁽¹⁾ Regulation 1272/2008 Eye Irrit. 2: H319; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning | Self-classified 7,5 - <10 % |
| CAS: 64742-95-6 EC: 918-668-5 Index: Non-applicable REACH: 01-2119455851-35-XXXX | Hydrocarbons, C9, aromatics⁽¹⁾ Regulation 1272/2008 Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger | Self-classified 2,5 - <5 % |
| CAS: Non-applicable EC: 927-632-8 Index: Non-applicable REACH: 01-2119457736-27-XXXX | Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics⁽¹⁾ Regulation 1272/2008 Asp. Tox. 1: H304; EUH066 - Danger | Self-classified 2,5 - <5 % |
| CAS: 125304-04-3 EC: Non-applicable Index: Non-applicable REACH: Non-applicable | Phenol, 2-(2H-Benzotriazol-2-yl)-6-Dodecyl-4-Methyl-, Branched and Linear⁽¹⁾ Regulation 1272/2008 Aquatic Chronic 2: H411 | Self-classified 1 - <1,5 % |
| CAS: Non-applicable EC: 915-687-0 Index: Non-applicable REACH: 01-2119491304-40-XXXX | Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate⁽¹⁾ Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1A: H317 - Warning | Self-classified 1 - <1,5 % |
| CAS: 1174627-68-9 EC: 700-204-6 Index: Non-applicable REACH: 01-2119497421-36-XXXX | methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate⁽¹⁾ Regulation 1272/2008 Eye Irrit. 2: H319 - Warning | Self-classified 1 - <1,5 % |
| CAS: 55406-53-6 EC: 259-627-5 Index: 616-212-00-7 REACH: 01-2120762115-60-XXXX | 3-iodo-2-propynyl Butylcarbamate⁽¹⁾ Regulation 1272/2008 Acute Tox. 3: H331; Acute Tox. 4: H302; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Sens. 1: H317; STOT RE 1: H372 - Danger | ATP ATP06 0,2 - <0,3 % |
| CAS: 34590-94-8 EC: 252-104-2 Index: Non-applicable REACH: 01-2119450011-60-XXXX | Dipropylene Glycol Methyl Ether⁽²⁾ Regulation 1272/2008 | Not classified 0,05 - <0,1 % |
| CAS: 7664-38-2 EC: 231-633-2 Index: 015-011-00-6 REACH: 01-2119485924-24-XXXX | Phosphoric acid⁽²⁾ Regulation 1272/2008 Skin Corr. 1B: H314 - Danger | ATP CLP00 0,01 - <0,02 % |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Substance with a Union workplace exposure limit

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS ** (continued)**

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

*** Changes with regards to the previous version*

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:**

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:****A.- Precautions for safe manipulation**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:**A.- Technical measures for storage**

| | |
|----------------|-----------|
| Minimum Temp.: | 5 °C |
| Maximum Temp.: | 40 °C |
| Maximum time: | 36 Months |

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

| Identification | Occupational exposure limits | | |
|--|------------------------------|--------|-----------------------|
| | IOELV (8h) | 50 ppm | 308 mg/m ³ |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | IOELV (STEL) | | |
| Phosphoric acid CAS: 7664-38-2 EC: 231-633-2 | IOELV (8h) | | 1 mg/m ³ |
| | IOELV (STEL) | | 2 mg/m ³ |

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|--|------------|------------------------|------------------------|-------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: 918-668-5 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 25 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 150 mg/m ³ | Non-applicable |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: Non-applicable EC: 915-687-0 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 0,5 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 0,68 mg/m ³ | Non-applicable |
| 3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 2 mg/kg | Non-applicable |
| | Inhalation | 0,07 mg/m ³ | 1,16 mg/m ³ | 0,023 mg/m ³ | 1,16 mg/m ³ |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 283 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 308 mg/m ³ | Non-applicable |
| Phosphoric acid CAS: 7664-38-2 EC: 231-633-2 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | 2 mg/m ³ | 10,7 mg/m ³ | 1 mg/m ³ |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|--|------------|----------------|----------------|------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: 918-668-5 | Oral | Non-applicable | Non-applicable | 11 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 11 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 32 mg/m ³ | Non-applicable |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: Non-applicable EC: 915-687-0 | Oral | Non-applicable | Non-applicable | 0,05 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 0,25 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 0,17 mg/m ³ | Non-applicable |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | Oral | Non-applicable | Non-applicable | 36 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 121 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 37,2 mg/m ³ | Non-applicable |
| Phosphoric acid CAS: 7664-38-2 EC: 231-633-2 | Oral | Non-applicable | Non-applicable | 0,1 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 4,57 mg/m ³ | 0,36 mg/m ³ |

PNEC:

| Identification | | | | |
|--|--------------|----------------|-------------------------|----------------|
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: Non-applicable EC: 915-687-0 | STP | 1 mg/L | Fresh water | 0,002 mg/L |
| | Soil | 0,21 mg/kg | Marine water | 0 mg/L |
| | Intermittent | 0,009 mg/L | Sediment (Fresh water) | 1,05 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,11 mg/kg |
| methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate CAS: 1174627-68-9 EC: 700-204-6 | STP | Non-applicable | Fresh water | Non-applicable |
| | Soil | 2,65 mg/kg | Marine water | Non-applicable |
| | Intermittent | Non-applicable | Sediment (Fresh water) | Non-applicable |
| | Oral | Non-applicable | Sediment (Marine water) | Non-applicable |

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT

Colours: 3800, 3801, 3802, 3803, 3806, 3809

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



| Identification | | | | |
|--|--------------|----------------|-------------------------|-------------|
| 3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5 | STP | 0,44 mg/L | Fresh water | 0,001 mg/L |
| | Soil | 0,005 mg/kg | Marine water | 0 mg/L |
| | Intermittent | 0,001 mg/L | Sediment (Fresh water) | 0,017 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,002 mg/kg |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | STP | 4168 mg/L | Fresh water | 19 mg/L |
| | Soil | 2,74 mg/kg | Marine water | 1,9 mg/L |
| | Intermittent | 190 mg/L | Sediment (Fresh water) | 70,2 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 7,02 mg/kg |

8.2 Exposure controls:



A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|-----------------------------------|--|---------------------|--|
|  Mandatory respiratory tract protection | Filter mask for gases and vapours |  | EN 405:2002+A1:2010 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands





| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|---|---|--|
|  Mandatory hand protection | NON-disposable chemical protective gloves |  | EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN 420:2004+A1:2010 | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|-------------|---|---|---|
|  Mandatory face protection | Face shield |  | EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|---|---|---|---|
|  Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties |  | EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
|  Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties |  | EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| | |
|---------------------------|---------------------------------|
| V.O.C. (Supply): | 37,75 % weight |
| V.O.C. density at 20 °C: | 400 kg/m ³ (400 g/L) |
| Average carbon number: | 9,86 |
| Average molecular weight: | 141,8 g/mol |

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

| | |
|--------------------------------------|---------------------------------|
| V.O.C. density at 20 °C: | 400 kg/m ³ (400 g/L) |
| EU limit for the product (Cat. A.E): | 400 g/L (2010) |
| Components: | Non-applicable |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|--|
| Physical state at 20 °C: | Liquid |
| Appearance: | Viscous |
| Colour: | According to the markings on the package |
| Odour: | Not available |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|--|-----------------------|
| Boiling point at atmospheric pressure: | 176 °C |
| Vapour pressure at 20 °C: | 463 Pa |
| Vapour pressure at 50 °C: | 2919,58 Pa (2,92 kPa) |
| Evaporation rate at 20 °C: | Non-applicable * |

Product description:

| | |
|--|-----------------------------|
| Density at 20 °C: | 860 - 900 kg/m ³ |
| Relative density at 20 °C: | 0,86 - 0,9 |
| Dynamic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 40 °C: | >20,5 cSt |
| Concentration: | Non-applicable * |
| pH: | Non-applicable * |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | |
| Solubility properties: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Decomposition temperature: Non-applicable *
 Melting point/freezing point: Non-applicable *
 Explosive properties: Non-applicable *
 Oxidising properties: Non-applicable *

Flammability:

Flash Point: 45 °C
 Heat of combustion: Non-applicable *
 Flammability (solid, gas): Non-applicable *
 Autoignition temperature: 246 °C
 Lower flammability limit: Not available
 Upper flammability limit: Not available

Explosive:

Lower explosive limit: Non-applicable *
 Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C: Non-applicable *
 Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 IARC: Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics (3); Hydrocarbons, C9, aromatics (3); 2,6-di-tert-butyl-p-cresol (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|--|----------------|----------------|--------|
| | LD50 oral | LD50 dermal | |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: Non-applicable EC: 915-687-0 | 3230 mg/kg | 3170 mg/kg | Rat |
| | Non-applicable | Non-applicable | Rabbit |
| | Non-applicable | Non-applicable | |
| Synthetic Silicon Dioxide CAS: 112945-52-5 EC: Non-applicable | 10000 mg/kg | 5100 mg/kg | Rat |
| | Non-applicable | Non-applicable | Rabbit |
| | Non-applicable | Non-applicable | |
| Hydrocarbons, C9-C11,n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: 64742-48-9 EC: 919-857-5 | 5100 mg/kg | Non-applicable | Rat |
| | Non-applicable | Non-applicable | |
| | Non-applicable | Non-applicable | |

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809
SECTION 11: TOXICOLOGICAL INFORMATION (continued)

| Identification | Acute toxicity | | Genus |
|--|----------------|----------------|---------------|
| | LD50 oral | LD50 dermal | |
| Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics CAS: Non-applicable EC: 927-632-8 | 5100 mg/kg | Non-applicable | Rat |
| 3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5 | 1100 mg/kg | 2100 mg/kg | Rat Rabbit |
| Phosphoric acid CAS: 7664-38-2 EC: 231-633-2 | 3500 mg/kg | 2470 mg/kg | Rat Rabbit |
| | Non-applicable | Non-applicable | |

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

| Identification | Acute toxicity | | Species | Genus |
|--|---------------------|------|-------------------------|------------|
| | LC50 | EC50 | | |
| Synthetic Silicon Dioxide CAS: 112945-52-5 EC: Non-applicable | 10000 mg/L (96 h) | | Brachydanio rerio | Fish |
| | 10000 mg/L (24 h) | | Daphnia magna | Crustacean |
| | Non-applicable | | | |
| Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC: 918-668-5 | >1 - 10 mg/L (96 h) | | | Fish |
| | >1 - 10 mg/L (48 h) | | | Crustacean |
| | >1 - 10 mg/L (72 h) | | | Algae |
| Phenol, 2-(2H-Benzotriazol-2-yl)-6-Dodecyl-4-Methyl-, Branched and Linear CAS: 125304-04-3 EC: Non-applicable | >1 - 10 mg/L (96 h) | | | Fish |
| | >1 - 10 mg/L (48 h) | | | Crustacean |
| | >1 - 10 mg/L (72 h) | | | Algae |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: Non-applicable EC: 915-687-0 | 0.9 mg/L (96 h) | | Danio rerio | Fish |
| | Non-applicable | | | |
| | 1.7 mg/L (72 h) | | N/A | Algae |
| 3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5 | 0.07 mg/L (96 h) | | Oncorhynchus mykiss | Fish |
| | 0.09 mg/L (96 h) | | Mysidopsis bahia | Crustacean |
| | 0.05 mg/L (72 h) | | Scenedesmus subspicatus | Algae |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | 10000 mg/L (96 h) | | Pimephales promelas | Fish |
| | 1919 mg/L (48 h) | | Daphnia magna | Crustacean |
| | Non-applicable | | | |

12.2 Persistence and degradability:

| Identification | Degradability | | Biodegradability | |
|--|----------------|-----|------------------|----------------|
| | BOD5 | COD | Concentration | Period |
| Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclics, <2% aromatics CAS: 64742-48-9 EC: 919-857-5 | Non-applicable | | Non-applicable | 28 days |
| | Non-applicable | | % Biodegradable | 80 % |
| | Non-applicable | | Concentration | 20 mg/L |
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate CAS: Non-applicable EC: 915-687-0 | Non-applicable | | Concentration | 28 days |
| | Non-applicable | | Period | 28 days |
| | Non-applicable | | % Biodegradable | 38 % |
| Dipropylene Glycol Methyl Ether CAS: 34590-94-8 EC: 252-104-2 | Non-applicable | | Concentration | Non-applicable |
| | 0 g O2/g | | Period | 28 days |
| | Non-applicable | | % Biodegradable | 73 % |

12.3 Bioaccumulative potential:

| Identification | Bioaccumulation potential | |
|--|---------------------------|----------|
| | BCF | Pow Log |
| 3-iodo-2-propynyl Butylcarbamate CAS: 55406-53-6 EC: 259-627-5 | 36 | 2.4 |
| | Potential | Moderate |

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809

SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Bioaccumulation potential | |
|---------------------------------|---------------------------|-------|
| Dipropylene Glycol Methyl Ether | BCF | 1 |
| CAS: 34590-94-8 | Pow Log | -0.06 |
| EC: 252-104-2 | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|--|-----------------------|--------------------|------------|-----------------------------|
| Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate | Koc | 204400 | Henry | 0E+0 Pa·m ³ /mol |
| CAS: Non-applicable | Conclusion | Immobile | Dry soil | No |
| EC: 915-687-0 | Surface tension | Non-applicable | Moist soil | No |
| methyl 5-(dimethylamino)-2-methyl-5-oxopentanoate | Koc | 18 | Henry | Non-applicable |
| CAS: 1174627-68-9 | Conclusion | Very High | Dry soil | Non-applicable |
| EC: 700-204-6 | Surface tension | 6,9E-2 N/m (23 °C) | Moist soil | Non-applicable |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Special regulations: 163, 367, 650
Tunnel restriction code: D/E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 223, 955, 163, 367
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: Non-applicable
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2021:



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 Transport hazard class(es):** 3
Labels: 3
- 14.4 Packing group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 3-iodo-2-propynyl Butylcarbamate.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 3-iodo-2-propynyl Butylcarbamate (Product-type 6, 7, 8, 9, 10, 13)

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809

SECTION 15: REGULATORY INFORMATION (continued)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|-------------------|-------------------------|-------------------------|
| P5c | FLAMMABLE LIQUIDS | 5000 | 50000 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:

- metallic glitter intended mainly for decoration,
- artificial snow and frost,
- “whoopee” cushions,
- silly string aerosols,
- imitation excrement,
- horns for parties,
- decorative flakes and foams,
- artificial cobwebs,
- stink bombs.

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:

'For professional users only'.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION
Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3):

- Removed substances
Cobalt bis(2-ethylhexanoate) (136-52-7)

Substances that contribute to the classification (SECTION 2):

- Removed substances
Cobalt bis(2-ethylhexanoate) (136-52-7)

Texts of the legislative phrases mentioned in section 2:

- H336: May cause drowsiness or dizziness.
- H412: Harmful to aquatic life with long lasting effects.
- H317: May cause an allergic skin reaction.
- H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

- CONTINUED ON NEXT PAGE -

M32 - LASUR SYNTHETIC PROTECTOR MATT
Colours: 3800, 3801, 3802, 3803, 3806, 3809**SECTION 16: OTHER INFORMATION (continued)**

Acute Tox. 3: H331 - Toxic if inhaled.
Acute Tox. 4: H302 - Harmful if swallowed.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
Skin Sens. 1A: H317 - May cause an allergic skin reaction.
STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

STOT SE 3: Calculation method
Aquatic Chronic 3: Calculation method
Skin Sens. 1A: Calculation method
Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon