



S60 - RUST PREVENTIVE PRIMER

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** S60 - RUST PREVENTIVE PRIMER
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
 Relevant uses: Printing
 Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
 Industrias Titán, S.A.U.
 Pol. Ind. Pratense, calle 114 nº 17-19
 08820 El Prat de Llobregat - Barcelona - España
 Phone.: +34 934 797 494 - Fax: +34 934 797 495
 msds@titanlux.es
 http://www.titanlux.es
- 1.4 Emergency telephone number:** +34 934 797 494 (7:30-14:30 h.) (working hours)

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
 Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
 Aerosol 1: Pressurised container: May burst if heated., H229
 Aerosol 1: Flammable aerosols, Category 1, H222
 Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
 Eye Irrit. 2: Eye irritation, Category 2, H319
 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
 Danger
- 

- Hazard statements:**
 Aerosol 1: H229 - Pressurised container: May burst if heated
 Aerosol 1: H222 - Extremely flammable aerosol
 Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects
 Eye Irrit. 2: H319 - Causes serious eye irritation
 STOT SE 3: H336 - May cause drowsiness or dizziness
- Precautionary statements:**
 P101: If medical advice is needed, have product container or label at hand
 P102: Keep out of reach of children
 P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P211: Do not spray on an open flame or other ignition source
 P251: Do not pierce or burn, even after use
 P260: Do not breathe spray
 P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
 P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
- Supplementary information:**
 EUH066: Repeated exposure may cause skin dryness or cracking
 EUH208: Contains 4-morpholinecarbaldehyde. May produce an allergic reaction
 EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist
- Substances that contribute to the classification**
 acetone; N-butyl acetate; 2-methoxy-1-methylethyl acetate
- Additional labeling:**

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 2: HAZARDS IDENTIFICATION ** (continued)

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture composed of additives, aggregates, pigments and resins in solvents

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | | Concentration |
|---|--|--|---------------|
| CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX | acetone⁽¹⁾ | ATP CLP00 | 25 - <50 % |
| | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger | |
| CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX | N-butyl acetate⁽¹⁾ | ATP CLP00 | 10 - <12,5 % |
| | Regulation 1272/2008 | Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning | |
| CAS: Non-applicable EC: 905-588-0 Index: Non-applicable REACH: 01-2119539452-40-XXXX | Reaction mass of ethylbenzene and xylene⁽¹⁾ | Self-classified | 2 - <2,5 % |
| | Regulation 1272/2008 | Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger | |
| CAS: 7779-90-0 EC: 231-944-3 Index: Non-applicable REACH: 01-2119485044-40-XXXX | trizinc bis(orthophosphate)⁽¹⁾ | ATP CLP00 | 2 - <2,5 % |
| | Regulation 1272/2008 | Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning | |
| CAS: 64-17-5 EC: 200-578-6 Index: 603-002-00-5 REACH: 01-2119457610-43-XXXX | ethanol⁽¹⁾ | Self-classified | 2 - <2,5 % |
| | Regulation 1272/2008 | Eye Irrit. 2: H319; Flam. Liq. 2: H225 - Danger | |
| CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX | 2-methoxy-1-methylethyl acetate⁽¹⁾ | Self-classified | 2 - <2,5 % |
| | Regulation 1272/2008 | Flam. Liq. 3: H226; STOT SE 3: H336 - Warning | |
| CAS: 13463-67-7 EC: 236-675-5 Index: Non-applicable REACH: 01-2119489379-17-XXXX | Titanium dioxide (aerodynamic diameter ≤ 10 µm)⁽¹⁾ | Self-classified | 2 - <2,5 % |
| | Regulation 1272/2008 | Carc. 2: H351 - Warning | |
| CAS: 4394-85-8 EC: 224-518-3 Index: Non-applicable REACH: 01-2119987993-12-XXXX | 4-morpholinecarbaldehyde⁽¹⁾ | Self-classified | 0,4 - <0,5 % |
| | Regulation 1272/2008 | Skin Sens. 1B: H317 - Warning | |
| CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX | 2-methoxy-1-methylethyl acetate⁽²⁾ | ATP ATP01 | 0,05 - <0,1 % |
| | Regulation 1272/2008 | Flam. Liq. 3: H226 - Warning | |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

⁽²⁾ Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

S60 - RUST PREVENTIVE PRIMER**SECTION 4: FIRST AID MEASURES****4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C
Maximum Temp.: 40 °C
Maximum time: 36 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace

| Identification | Occupational exposure limits | | |
|---|------------------------------|---------|------------------------|
| | IOELV (8h) | 500 ppm | 1210 mg/m ³ |
| acetone CAS: 67-64-1 EC: 200-662-2 | IOELV (STEL) | | |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | IOELV (8h) | 50 ppm | 241 mg/m ³ |
| | IOELV (STEL) | 150 ppm | 723 mg/m ³ |
| Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0 | IOELV (8h) | 50 ppm | 221 mg/m ³ |
| | IOELV (STEL) | 100 ppm | 442 mg/m ³ |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | IOELV (8h) | 50 ppm | 275 mg/m ³ |
| | IOELV (STEL) | 100 ppm | 550 mg/m ³ |
| 2-methoxy-1-methylethyl acetate CAS: 108-65-6 EC: 203-603-9 | IOELV (8h) | 50 ppm | 275 mg/m ³ |
| | IOELV (STEL) | 100 ppm | 550 mg/m ³ |

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|--|------------|-----------------------|------------------------|------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| acetone CAS: 67-64-1 EC: 200-662-2 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 186 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | 2420 mg/m ³ | 1210 mg/m ³ | Non-applicable |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | 11 mg/kg | Non-applicable | 11 mg/kg | Non-applicable |
| | Inhalation | 600 mg/m ³ | 600 mg/m ³ | 300 mg/m ³ | 300 mg/m ³ |
| trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 83 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 5 mg/m ³ | Non-applicable |
| ethanol CAS: 64-17-5 EC: 200-578-6 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 343 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 950 mg/m ³ | Non-applicable |
| 4-morpholinecarbaldehyde CAS: 4394-85-8 EC: 224-518-3 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 11,7 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 50,3 mg/m ³ | 13,3 mg/m ³ |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|--|------------|-----------------------|-----------------------|------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| acetone CAS: 67-64-1 EC: 200-662-2 | Oral | Non-applicable | Non-applicable | 62 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 62 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 200 mg/m ³ | Non-applicable |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | Oral | 2 mg/kg | Non-applicable | 2 mg/kg | Non-applicable |
| | Dermal | 6 mg/kg | Non-applicable | 6 mg/kg | Non-applicable |
| | Inhalation | 300 mg/m ³ | 300 mg/m ³ | 35,7 mg/m ³ | 35,7 mg/m ³ |
| trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3 | Oral | Non-applicable | Non-applicable | 0,83 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 83 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 2,5 mg/m ³ | Non-applicable |
| ethanol CAS: 64-17-5 EC: 200-578-6 | Oral | Non-applicable | Non-applicable | 87 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 206 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 114 mg/m ³ | Non-applicable |
| 4-morpholinecarbaldehyde CAS: 4394-85-8 EC: 224-518-3 | Oral | Non-applicable | Non-applicable | 4,17 mg/kg | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 4,17 mg/kg | Non-applicable |
| | Inhalation | Non-applicable | Non-applicable | 8,93 mg/m ³ | 13,3 mg/m ³ |

PNEC:

| Identification | | | | | |
|--|--------------|----------------|-------------------------|-------------|--|
| acetone CAS: 67-64-1 EC: 200-662-2 | STP | 100 mg/L | Fresh water | 10,6 mg/L | |
| | Soil | 29,5 mg/kg | Marine water | 1,06 mg/L | |
| | Intermittent | 21 mg/L | Sediment (Fresh water) | 30,4 mg/kg | |
| | Oral | Non-applicable | Sediment (Marine water) | 3,04 mg/kg | |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | STP | 35,6 mg/L | Fresh water | 0,18 mg/L | |
| | Soil | 0,09 mg/kg | Marine water | 0,018 mg/L | |
| | Intermittent | 0,36 mg/L | Sediment (Fresh water) | 0,981 mg/kg | |
| | Oral | Non-applicable | Sediment (Marine water) | 0,098 mg/kg | |
| trizinc bis(orthophosphate) CAS: 7779-90-0 EC: 231-944-3 | STP | 0,1 mg/L | Fresh water | 0,0206 mg/L | |
| | Soil | 35,6 mg/kg | Marine water | 0,0061 mg/L | |
| | Intermittent | Non-applicable | Sediment (Fresh water) | 117,8 mg/kg | |
| | Oral | Non-applicable | Sediment (Marine water) | 56,5 mg/kg | |

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification | | | | |
|---|--------------|----------------|-------------------------|-------------|
| ethanol CAS: 64-17-5 EC: 200-578-6 | STP | 580 mg/L | Fresh water | 0,96 mg/L |
| | Soil | 0,63 mg/kg | Marine water | 0,79 mg/L |
| | Intermittent | 2,75 mg/L | Sediment (Fresh water) | 3,6 mg/kg |
| | Oral | 0,38 g/kg | Sediment (Marine water) | 2,9 mg/kg |
| 4-morpholinecarbaldehyde CAS: 4394-85-8 EC: 224-518-3 | STP | 2000 mg/L | Fresh water | 0,5 mg/L |
| | Soil | 0,244 mg/kg | Marine water | 0,05 mg/L |
| | Intermittent | 5 mg/L | Sediment (Fresh water) | 2,69 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,269 mg/kg |



8.2 Exposure controls:

A.- General security and hygiene measures in the work place



As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|--|---|--|---|
|  Mandatory respiratory tract protection | Filter mask for gases, vapours and particles |  CAT III | EN 149:2001+A1:2009 EN 405:2001+A1:2009 | Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected. |

C.- Specific protection for the hands





| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|--|---|--|
|  Mandatory hand protection | NON-disposable chemical protective gloves |  CAT III | EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009 | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. |

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|-------------|---|---|---|
|  Mandatory face protection | Face shield |  CAT II | EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|---|--|---|---|
|  Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties |  CAT III | EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
|  Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties |  CAT III | EN ISO 13287:2012 EN ISO 20345:2011 EN 13832-1:2019 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |
| Emergency shower | | Eyewash stations | |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

| | |
|---------------------------|-------------------------------------|
| V.O.C. (Supply): | 88,7 % weight |
| V.O.C. density at 20 °C: | 702,1 kg/m ³ (702,1 g/L) |
| Average carbon number: | 3,83 |
| Average molecular weight: | 73,05 g/mol |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|------------------|
| Physical state at 20 °C: | Aerosol |
| Appearance: | Not available |
| Colour: | Not available |
| Odour: | Not available |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|--|----------------------|
| Boiling point at atmospheric pressure: | -42 °C (Propellant) |
| Vapour pressure at 20 °C: | Non-applicable * |
| Vapour pressure at 50 °C: | <300000 Pa (300 kPa) |
| Evaporation rate at 20 °C: | Non-applicable * |

Product description:

| | |
|--|------------------|
| Density at 20 °C: | Non-applicable * |
| Relative density at 20 °C: | Non-applicable * |
| Dynamic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 40 °C: | Non-applicable * |
| Concentration: | Non-applicable * |
| pH: | Non-applicable * |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Non-applicable * |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |
| Recipient pressure: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

| | |
|-------------------------------|----------------------|
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |
| Flammability: | |
| Flash Point: | -104 °C (Propellant) |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | 365 °C (Propellant) |
| Lower flammability limit: | 1,2 % Volume |
| Upper flammability limit: | 13 % Volume |
| Explosive: | |
| Lower explosive limit: | Non-applicable * |
| Upper explosive limit: | Non-applicable * |
| 9.2 Other information: | |
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
IARC: Talc (3); ethanol (1); Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$) (2B); Diiron trioxide (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter $\leq 10 \mu\text{m}$): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|--|-----------------|-----------------|--------|
| acetone CAS: 67-64-1 EC: 200-662-2 | LD50 oral | 5800 mg/kg | Rat |
| | LD50 dermal | 7426 mg/kg | Rabbit |
| | LC50 inhalation | 76 mg/L (4 h) | Rat |
| N-butyl acetate CAS: 123-86-4 EC: 204-658-1 | LD50 oral | 12789 mg/kg | Rat |
| | LD50 dermal | 14112 mg/kg | Rabbit |
| | LC50 inhalation | 23,4 mg/L (4 h) | Rat |
| Reaction mass of ethylbenzene and xylene CAS: Non-applicable EC: 905-588-0 | LD50 oral | 2100 mg/kg | Rat |
| | LD50 dermal | 1100 mg/kg | Rat |
| | LC50 inhalation | 11 mg/L (4 h) | Rat |

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

| Identification | Acute toxicity | | Genus |
|---|-----------------|------------------|--------|
| ethanol | LD50 oral | 6200 mg/kg | Rat |
| CAS: 64-17-5 | LD50 dermal | 20000 mg/kg | Rabbit |
| EC: 200-578-6 | LC50 inhalation | 124,7 mg/L (4 h) | Rat |
| 2-methoxy-1-methylethyl acetate | LD50 oral | 8532 mg/kg | Rat |
| CAS: 108-65-6 | LD50 dermal | 5100 mg/kg | Rat |
| EC: 203-603-9 | LC50 inhalation | 30 mg/L (4 h) | Rat |
| Titanium dioxide (aerodynamic diameter ≤ 10 µm) | LD50 oral | 10000 mg/kg | Rat |
| CAS: 13463-67-7 | LD50 dermal | 10000 mg/kg | Rabbit |
| EC: 236-675-5 | LC50 inhalation | Non-applicable | |
| 4-morpholinecarbaldehyde | LD50 oral | 7475 mg/kg | Rat |
| CAS: 4394-85-8 | LD50 dermal | 18400 mg/kg | Rabbit |
| EC: 224-518-3 | LC50 inhalation | Non-applicable | |
| 2-methoxy-1-methylethyl acetate | LD50 oral | 8532 mg/kg | Rat |
| CAS: 108-65-6 | LD50 dermal | 5100 mg/kg | Rat |
| EC: 203-603-9 | LC50 inhalation | 30 mg/L (4 h) | Rat |

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

| Identification | Acute toxicity | | Species | Genus |
|--|----------------|---------------------|-------------------------|------------|
| acetone | LC50 | 5540 mg/L (96 h) | Oncorhynchus mykiss | Fish |
| CAS: 67-64-1 | EC50 | 23.5 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 200-662-2 | EC50 | 3400 mg/L (48 h) | Chlorella pyrenoidosa | Algae |
| N-butyl acetate | LC50 | 62 mg/L (96 h) | Leuciscus idus | Fish |
| CAS: 123-86-4 | EC50 | 73 mg/L (24 h) | Daphnia magna | Crustacean |
| EC: 204-658-1 | EC50 | 675 mg/L (72 h) | Scenedesmus subspicatus | Algae |
| Reaction mass of ethylbenzene and xylene | LC50 | 13.5 mg/L (96 h) | Oncorhynchus mykiss | Fish |
| CAS: Non-applicable | EC50 | 0.6 mg/L (96 h) | Gammarus lacustris | Crustacean |
| EC: 905-588-0 | EC50 | 10 mg/L (72 h) | Skeletonema costatum | Algae |
| trizinc bis(orthophosphate) | LC50 | 0.1 - 1 mg/L (96 h) | | Fish |
| CAS: 7779-90-0 | EC50 | 0.1 - 1 mg/L | | Crustacean |
| EC: 231-944-3 | EC50 | 0.1 - 1 mg/L | | Algae |
| ethanol | LC50 | 11000 mg/L (96 h) | Alburnus alburnus | Fish |
| CAS: 64-17-5 | EC50 | 9268 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 200-578-6 | EC50 | 1450 mg/L (192 h) | Microcystis aeruginosa | Algae |
| 2-methoxy-1-methylethyl acetate | LC50 | 161 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 108-65-6 | EC50 | 481 mg/L (48 h) | Daphnia sp. | Crustacean |
| EC: 203-603-9 | EC50 | Non-applicable | | |
| 4-morpholinecarbaldehyde | LC50 | 500 mg/L (96 h) | Leuciscus idus | Fish |
| CAS: 4394-85-8 | EC50 | Non-applicable | | |
| EC: 224-518-3 | EC50 | 23880 mg/L (72 h) | Desmodesmus subspicatus | Algae |
| 2-methoxy-1-methylethyl acetate | LC50 | 161 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 108-65-6 | EC50 | 481 mg/L (48 h) | Daphnia sp. | Crustacean |
| EC: 203-603-9 | EC50 | Non-applicable | | |

12.2 Persistence and degradability:

| Identification | Degradability | | Biodegradability | |
|----------------|---------------|----------------|------------------|----------|
| acetone | BOD5 | Non-applicable | Concentration | 100 mg/L |
| CAS: 67-64-1 | COD | Non-applicable | Period | 28 days |
| EC: 200-662-2 | BOD5/COD | 0.96 | % Biodegradable | 96 % |

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Degradability | | Biodegradability | |
|---------------------------------|---------------|----------------|------------------|----------------|
| N-butyl acetate | BOD5 | Non-applicable | Concentration | Non-applicable |
| CAS: 123-86-4 | COD | Non-applicable | Period | 5 days |
| EC: 204-658-1 | BOD5/COD | 0.79 | % Biodegradable | 84 % |
| ethanol | BOD5 | Non-applicable | Concentration | 100 mg/L |
| CAS: 64-17-5 | COD | Non-applicable | Period | 14 days |
| EC: 200-578-6 | BOD5/COD | 0.57 | % Biodegradable | 89 % |
| 2-methoxy-1-methylethyl acetate | BOD5 | Non-applicable | Concentration | 785 mg/L |
| CAS: 108-65-6 | COD | Non-applicable | Period | 8 days |
| EC: 203-603-9 | BOD5/COD | Non-applicable | % Biodegradable | 100 % |
| 4-morpholinecarbaldehyde | BOD5 | Non-applicable | Concentration | 100 mg/L |
| CAS: 4394-85-8 | COD | Non-applicable | Period | 30 days |
| EC: 224-518-3 | BOD5/COD | Non-applicable | % Biodegradable | 100 % |
| 2-methoxy-1-methylethyl acetate | BOD5 | Non-applicable | Concentration | 785 mg/L |
| CAS: 108-65-6 | COD | Non-applicable | Period | 8 days |
| EC: 203-603-9 | BOD5/COD | Non-applicable | % Biodegradable | 100 % |

12.3 Bioaccumulative potential:

| Identification | Bioaccumulation potential | |
|--|---------------------------|-------|
| acetone | BCF | 1 |
| CAS: 67-64-1 | Pow Log | -0.24 |
| EC: 200-662-2 | Potential | Low |
| N-butyl acetate | BCF | 4 |
| CAS: 123-86-4 | Pow Log | 1.78 |
| EC: 204-658-1 | Potential | Low |
| Reaction mass of ethylbenzene and xylene | BCF | 9 |
| CAS: Non-applicable | Pow Log | 2.77 |
| EC: 905-588-0 | Potential | Low |
| ethanol | BCF | 3 |
| CAS: 64-17-5 | Pow Log | -0.31 |
| EC: 200-578-6 | Potential | Low |
| 2-methoxy-1-methylethyl acetate | BCF | 1 |
| CAS: 108-65-6 | Pow Log | 0.43 |
| EC: 203-603-9 | Potential | Low |
| 4-morpholinecarbaldehyde | BCF | 1 |
| CAS: 4394-85-8 | Pow Log | -1.2 |
| EC: 224-518-3 | Potential | Low |
| 2-methoxy-1-methylethyl acetate | BCF | 1 |
| CAS: 108-65-6 | Pow Log | 0.43 |
| EC: 203-603-9 | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|-----------------|-----------------------|----------------------|------------|--------------------------------|
| acetone | Koc | 1 | Henry | 2,93 Pa·m ³ /mol |
| CAS: 67-64-1 | Conclusion | Very High | Dry soil | Yes |
| EC: 200-662-2 | Surface tension | 2,304E-2 N/m (25 °C) | Moist soil | Yes |
| N-butyl acetate | Koc | Non-applicable | Henry | Non-applicable |
| CAS: 123-86-4 | Conclusion | Non-applicable | Dry soil | Non-applicable |
| EC: 204-658-1 | Surface tension | 2,478E-2 N/m (25 °C) | Moist soil | Non-applicable |
| ethanol | Koc | 1 | Henry | 4,61E-1 Pa·m ³ /mol |
| CAS: 64-17-5 | Conclusion | Very High | Dry soil | Yes |
| EC: 200-578-6 | Surface tension | 2,339E-2 N/m (25 °C) | Moist soil | Yes |

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Absorption/desorption | | Volatility | |
|--------------------------|-----------------------|----------------|------------|---------------------------------|
| 4-morpholinecarbaldehyde | Koc | 1 | Henry | 2,302E-3 Pa·m ³ /mol |
| CAS: 4394-85-8 | Conclusion | Very High | Dry soil | No |
| EC: 224-518-3 | Surface tension | Non-applicable | Moist soil | No |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 16 05 04* | gases in pressure containers (including halons) containing hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



- 14.1 UN number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS, flammable
- 14.3 Transport hazard class(es):** 2
- Labels:** 2.1
- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
 - Special regulations: 190, 327, 344, 625
 - Tunnel restriction code: D
 - Physico-Chemical properties: see section 9
 - Limited quantities: 1 L
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1950
14.2 UN proper shipping name: AEROSOLS, flammable
14.3 Transport hazard class(es): 2
 Labels: 2.1
14.4 Packing group: N/A
14.5 Environmental hazards: No
14.6 Special precautions for user
 Special regulations: 63, 959, 190, 277, 327, 344
 EmS Codes: F-D, S-U
 Physico-Chemical properties: see section 9
 Limited quantities: 1 L
 Segregation group: Non-applicable
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2020:



- 14.1 UN number:** UN1950
14.2 UN proper shipping name: AEROSOLS, flammable
14.3 Transport hazard class(es): 2
 Labels: 2.1
14.4 Packing group: N/A
14.5 Environmental hazards: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|--------------------|-------------------------|-------------------------|
| P3a | FLAMMABLE AEROSOLS | 150 | 500 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Regulation (EU) No 98/2013 of the European Parliament and of the Council of 15 January 2013 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

- CONTINUED ON NEXT PAGE -

S60 - RUST PREVENTIVE PRIMER

SECTION 15: REGULATORY INFORMATION (continued)

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

- Precautionary statements

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation

H336: May cause drowsiness or dizziness

H412: Harmful to aquatic life with long lasting effects

H229: Pressurised container: May burst if heated

H222: Extremely flammable aerosol

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled

Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways

Carc. 2: H351 - Suspected of causing cancer (Inhalation)

Eye Irrit. 2: H319 - Causes serious eye irritation

Flam. Liq. 2: H225 - Highly flammable liquid and vapour

Flam. Liq. 3: H226 - Flammable liquid and vapour

Skin Irrit. 2: H315 - Causes skin irritation

Skin Sens. 1B: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure

STOT SE 3: H335 - May cause respiratory irritation

STOT SE 3: H336 - May cause drowsiness or dizziness

Classification procedure:

Eye Irrit. 2: Calculation method

STOT SE 3: Calculation method

Aquatic Chronic 3: Calculation method

Aerosol 1: Calculation method

Aerosol 1: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

- CONTINUED ON NEXT PAGE -



Safety data sheet

According to 1907/2006/EC (REACH), 2015/830/EU (THIS SDS IS JUST FOR INFORMATIVE PURPOSE. THE SDS SHALL BE SUPPLIED IN AN OFFICIAL LANGUAGE OF THE COUNTRY WHERE THE PRODUCT IS PLACED ON THE MARKET)

S60 - RUST PREVENTIVE PRIMER

SECTION 16: OTHER INFORMATION (continued)

EC₅₀: Effective concentration 50

Log-POW: Octanol-water partition coefficient

K_{oc}: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -