

# SERVICOLOR PREMIER ECO-RANGE BASE TITANLUX. SYNTHETIC ENAMEL

Indoor - Outdoor. Gloss. W1 White Base.



Product Code: 001 0571

## Description

Bases for preparing paint to be coloured with the SERVICOLOR tinting systems. Synthetic enamel. Based on high solids technology. Quick-drying. Multi-Purpose. High gloss. Elastic. Excellent colour and gloss stability. High resistance to scratching. Good levelling and edge coverage. Resistant to weathering, grease, washes, etc.

## Fields of Application

For indoor and outdoor use. To protect and embellish doors, furniture, industrial vehicles, machinery, etc.

## Technical Data

<b>Product Type</b>	High solid alkyd
<b>Finish</b>	Gloss
<b>Colour (UNE EN ISO 11664-4)</b>	White
<b>Density (UNE EN ISO 2811-1)</b>	1.03 - 1.05 Kg/l
<b>Coverage (UNE 48282)</b>	12 - 14 m <sup>2</sup> /l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	4 - 5 hours
<b>Recoat time at 23°C 60% RH (UNE 48283)</b>	18 - 24 hours
<b>Methods of Application</b>	Brush, roller and spray-gun
<b>Equipment Cleaning</b>	Odourless Thinner or White Spirit
<b>Application Temperature, RH&lt;80%</b>	+10°C - +30°C
<b>Flash Point (UNE EN ISO 3679)</b>	40 - 42 °C
<b>Volume Solids (UNE EN ISO 3233-3)</b>	50 - 52 %
<b>VOC (UNE EN ISO 11890-2)</b>	2.004/42/IIA (d) (400/300) Max. COV 300 g/l
<b>Pack sizes</b>	4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Thoroughly stir the contents in the can.

The surfaces to be painted have to be clean, dry and suitably primed.

Remove all existing rests of dirt, grease, poorly adhered rust and previous coatings by using thinner or paint stripper, depending on requirements.

If the temperature of the surface is below 10°C and if paint coat is thick, the overcoating time has to be longer. Check that the surface is suitably dry before overcoating.

## BARE SURFACES:

Wood: Sand wood following the wood grain, thoroughly clean, remove all resins or resin secretion on the surface and smooth up sharp edges. Apply TITAN Sealing-Primer or Multi-Purpose Primer depending on requirements.

Iron and steel: TITANLUX Synthetic Rust-Preventive Primer or TITAN Multi-Purpose Primer. For outdoor surfaces, at least two coats of the selected primer will be needed. For indoor surfaces, one coat will be enough.

Other surfaces: Please consult your dealer.

In all cases for:

Indoor surfaces: Finish with 1 or 2 coats of TITANLUX Synthetic Enamel.

Outdoor surfaces: Finish with 2 or 3 coats of TITANLUX Synthetic Enamel.

## MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, lightly sand and directly apply 1 or 2 coats of TITANLUX Synthetic Enamel.

## MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Completely remove all previous paint coats and proceed as for bare surfaces.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Recommended maximum storage time: 24 months after the date of manufacture in original and perfectly sealed packaging at temperatures between 5 and 35°C.

Issue date: 2014-01

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



# TITAN

**INDUSTRIAS TITAN S.A.U.**  
España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764



001 0571 - SERVICOLOR PREMIER ECO-RANGE BASE TITANLUX. SYNTHETIC ENAMEL