

TITANLUX READY-TO-USE MATT

Indoors. Matt



Product Code: 016

Description

Quick-drying synthetic paint. Extremely hard and resistant to washing. Tough, with a fine velvety matt look. Easy application.

Fields of Application

For indoor use. Highly suitable for decorating walls, ceilings, doors, furniture, heating radiators, etc.

Technical Data

Product Type	Modified alkyd
Colour (UNE EN ISO 11664-4)	White
Density (UNE EN ISO 2811-1)	1.75 - 1.77 Kg/l
Coverage (UNE 48282)	10 - 15 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	4 - 8 h
Recoat time at 23°C 60% RH (UNE 48283)	24 hours
Methods of Application	Brush (for retouching and small areas) and roller
Equipment Cleaning	TITAN Odourless Thinner or White Spirit
Tinting	TITAN Universal Tinting Colours
Flash Point (UNE EN ISO 3679)	46 °C
Volume Solids (UNE EN ISO 3233-3)	57 - 58%
VOC (UNE EN ISO 11890-2)	2.004/42IIA (d) (400/300) Max. COV 300 g/l
Pack sizes	4 l, 750 ml and 375 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Stir well before using.

The surfaces to be painted have to be clean, dry and sound.

BARE SURFACES:

Plaster and Wood: TITAN Sealing Primer, as it is or coloured with TITAN Universal Tinting Colours. In most cases, one topcoat will be enough.

Iron: TITANLUX Synthetic Rust-Preventive Primer or TITAN Multi-Purpose Primer.

Distemper or whitewash: TITAN HIDROLIN before the basecoat of TITAN Sealing Primer.

Other surfaces: Please seek advice.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, lightly sand and directly apply TITANLUX Ready-to-Use Matt Paint.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Completely remove all previous paint coats and proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2014-01

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

016 - TITANLUX READY-TO-USE MATT

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

