

TITAN FOR WRITING BOARDS

Indoors - Semi Matt



Product Code: 01B



Description

Synthetic semi-matt paint. Good levelling. It prevents blur. Wash resistant.

Fields of Application

For the painting and maintenance of school boards. Highly suitable for decorating indoor rooms (kitchens, children rooms, offices, schools, museums, restaurants....) on walls, columns, doors, furniture, cupboards, electric appliances and small decorative elements, when writing with chalk sticks is required.

Technical Data

Product Type	Alkyd urethaned
Finish	Semi matt
Colour (UNE EN ISO 11664-4)	Black and Green
Density (UNE EN ISO 2811-1)	1,28 - 1,31 Kg/l
Coverage	10 - 12 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	3 - 4 hours
Recoat time at 23°C 60% RH (UNE 48283)	24 hours
Methods of Application	Brush and roller
Equipment Cleaning	TITAN Turpentine or White Spirit
Flash Point (UNE EN ISO 3679)	40 - 42 °C
Volume Solids (UNE EN ISO 3233-3)	46 - 48 %
VOC (UNE EN ISO 11890-2)	2.004/42IIA (i) (600/500) Max. COVs 400 g/l
Pack sizes	750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Stir well before using. The surfaces to be painted have to be clean, dry and suitably primed. Let to dry at least for 2 - 3 days before using the school board. For a suitable performance, after 3 days, it is advisable to wash the surface with soapy water. Only intended for writing with chalk sticks.

Cleaning: With an eraser. When deeper cleaning is required, use a moistened rag.

IMPORTANT:

Writing board effect for traditional soft chalk. Hard chalk (also called anti-dust) can scratch the surface.

Coloured chalk sticks: They may stain the writing surface because they contain wax. These stains may be removed with a moistened rag and some soft detergent. Avoid too strong soap.

BARE SURFACES:

Plaster: TITAN Sealing Primer or Multi-Purpose Primer.

Wood: TITAN Protector, Sealing-Primer or Multi-Purpose Primer.

Iron: TITANLUX Synthetic Rust-Preventive Primer or TITAN Multi-Purpose Primer..

Other surfaces: Please consult your dealer.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, lightly sand and directly apply TITAN Paint for Writing Boards.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Completely remove all previous paint coats and proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-06

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona (España)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

