

WATER BASED ENAMEL FOR WRITING BOARDS TITANLUX

Indoor. Matt



Product Code: 01P

Description

Matt enamel. Very high levelling, anti-reflective, wash resistant and with very low odour.

Ideal for decoration in interior rooms, walls, doors, furniture, electrical appliances and small decorative elements on which you want to write or draw with chalk.

Technical Data

Product Type	Acrylic
Finish	Matt
Colour (UNE EN ISO 11664-4)	Black
Density (UNE EN ISO 2811-1)	1.14 - 1.18 Kg/l
Coverage	8 - 12 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	1 - 2 hours
Recoat time at 23°C 60% RH (UNE 48283)	6 - 12 hours
Methods of Application	Brush, roller and spray-gun
Thinner	Water
Application Temperature, RH<80%	+10°C - +30°C.
Tinting	TITANCOLOR System
Volume Solids (UNE EN ISO 3233-3)	34.5 - 35.5 %
VOC (UNE EN ISO 11890-2)	2.004/42IIA (d) (150/130) Max. VOC 90 g/l.
Pack sizes	750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Thoroughly stir the contents in the pack. The surfaces to be painted have to be clean, dry and suitably primed. Remove all existing rests of dirt, grease, poorly adhered rust and previous coatings by using thinner or paint stripper, depending on requirements.

Wait at least 5 days before using the painted surface as a writing board.

BARE SURFACES:

Important remark: Use traditional soft chalk or fluid ink markers (preferably in white). Hard chalk (also called anti-dust) can scratch the surface.

It is recommended to remove the chalk with a damp cloth.

On most surfaces you can directly apply Titanlux Water Based Enamel for Writing Boards. On highly porous or metal surfaces, seal or prime the surface with Water Based Multi Purpose Primer. Finish with 2 coats of Titanlux Water Based Enamel for Writing Boards.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, lightly sand and directly apply 1 or 2 coats of Titanlux Water Based Enamel for Writing Boards.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Thoroughly remove all previous coats and proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2021-06

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158



AkzoNobel

