

TITAN PAINT FOR FLOORS

Indoors. Gloss



Product Code: 023

Description

Gloss-finish polyurethane paint. Long-lasting due to its high resistance to marring. Easy application and quick drying. It resists spots of oil, fruit, lye, etc. Perfectly washable, even with hot water., etc.

Fields of Application

Appropriate for decoration and renovation of old or marred pavements of tiles, concrete and alike at home, shops, stores, etc. Indoor use.

Technical Data

Product Type	Synthetic urethaned
Finish	Gloss
Colour (UNE EN ISO 11664-4)	English red
Density (UNE EN ISO 2811-1)	1.03 - 1.05 Kg/l
Coverage	11 - 15 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	4 - 5 hours
Recoat time at 23°C 60% RH (UNE 48283)	10 hours. Suitable for use: 24 hours
Methods of Application	Brush and roller
Equipment Cleaning	Synthetics and Grease Thinner
Application Temperature, RH<80%	+10 °C - +30 °C
Flash Point (UNE EN ISO 3679)	46 °C
Volume Solids (UNE EN ISO 3233-3)	48 - 49%
VOC (UNE EN ISO 11890-2)	2.004/42IIA (i) (600/500) Max COV 450 g/l
Pack sizes	4 l y 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Stir well before using.

The surfaces to be painted have to be clean, dry and suitably primed.

This paint is unsuitable for application on glossy mosaic pavements..

BARE SURFACES:

Porous tile, old mosaic pavements: If floors have been treated with waxes or polishing products or are greasy, wash them with a 10% sodium phosphate solution in hot water; rinse with abundant water and let to thoroughly dry (minimum 48 hours). Clean with TITAN Turpentine to remove any trace of waxes or grease. If elimination is not total, a defective adhesion of

paint will be produced.

After thoroughly cleaning and removing dust, apply TITAN Paint for Floors by thin coats.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, lightly sand, remove dust and directly apply one thin coat of TITAN Paint for Floors.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Completely remove all previous paint coats and proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-09

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

023 - TITAN PAINT FOR FLOORS

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

