

TITAN BATHROOMS AND KITCHENS

Indoor. Matt



Product Code: 026

Description

Matt indoor emulsion paint for protecting and decorating walls and ceilings. Ideal for application on walls and ceilings, and especially for home bathrooms and kitchens because of its high coverage and resistance to stains caused by grease and dampness. It contains anti mould preservative.

Technical Data

Product Type	Acrylic styrene
Finish	Matt
Colour (UNE EN ISO 11664-4)	White
Density (UNE EN ISO 2811-1)	1.52 - 1.58 Kg/l
Coverage (UNE 48282)	3 - 8 m ² /l (70 - 110 dry microns)
Drying at 23°C 60 % RH (UNE 48301)	30 - 60 minutes
Recoat time at 23°C 60% RH (UNE 48283)	6 - 8 hours
Methods of Application	Brush, roller and spray-gun
Thinner	Water
Recommended Thickness (UNE EN ISO 2808)	140 - 220 dry microns in two coats
Application Temperature, RH<80%	+10°C - +30 °C.
Tinting	TITAN Universal Tinting Colours, Professional Water-based Dye or Servicolor System
Volume Solids (UNE EN ISO 3233-3)	43 - 44 %
VOC (UNE EN ISO 11890-2)	2004/42/IIA (c) (75/40) Max. COV 18 g/l
Pack sizes	4 l (rectangular bucket) and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Certificates

Determination of contrast (hiding power) UNE-EN-ISO 6504-3: Class 1 Hiding power according to EN 13300 (two coats of paint at a coverage rate of 4.5 m²/l)

Wet-Scrub Resistance, UNE EN ISO 11998: Class 2 wash resistance according to EN 13300

Directions for use

GENERAL REMARKS:

Thoroughly stir the contents in the pack. The surfaces to be painted have to be clean, dry and sound.

BARE SURFACES:

If the surfaces are in good condition, apply a first coat thinned with 10 - 15% water. Apply a second unthinned coat.

If the surfaces are in poor condition, repair all the damaged areas, remove all poorly adhered particles and material. Clean all existing dirt and dust.

In order to homogenise porosity and improve the finish, as well as on distemper and size paints, whitewash or the surfaces where these have been removed, it is recommended to apply a first coat of A18 Water-based Sealing Primer or A19 Water-based Fixative, strictly following the directions for use stated in their technical sheets..

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Directly apply the paint after previous washing or brushing. Thin the first coat with 10 - 15% water. Apply a second unthinned coat.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Thoroughly remove old paint coats and proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

It contains BCM, IPU, IPBC, Terbutryn, to protect the initial properties of the treated article.

Protect the packs from temperatures below 0°C

Issue date: 2015-11

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

026 - TITAN BATHROOMS AND KITCHENS

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

