

TITANLUX WATER-BASED VARNISH STAIN DECO

Indoors. Satin



Product Code: 04F

Description

Water-based polyurethane satin-finish varnish-stain to tint, protect, embellish, restore and decorate any kind of wood surface. Hard-wearing, high resistance. Very elastic.

Fields of Application

To tint, varnish, restore and decorate any kind of indoor wooden surface, such as furniture, doors, cupboards, etc.

Technical Data

Product Type	Polyurethane
Finish	Satin
Colour (UNE EN ISO 11664-4)	Clear and colour range
Density (UNE EN ISO 2811-1)	1.04 - 1.07 Kg/l
Coverage (UNE 48282)	10 - 16 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	30 - 60 minutes
Recoat time at 23°C 60% RH (UNE 48283)	4 - 6 hours
Methods of Application	Brush
Thinning	5 - 10 % (1st coat, unvarnished wood)
Thinner	Water
Equipment Cleaning	Water
Application Temperature, RH<80%	+10°C - +30°C
Volume Solids (UNE EN ISO 3233-3)	28 - 30%
VOC (UNE EN ISO 11890-2)	2.004/42IIA (e) (150/130) Max. COV 65 g/l.
Pack sizes	500 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Thoroughly stir the contents in the can and apply by thin coats, on smooth (sanded), clean and dry surfaces, thinning if necessary. Lightly sand between coats to achieve a perfect finish.

Tropical or resinous wood: Please refer to the Technical Service.

BARE SURFACES:

Apply 2 - 3 coats; If the required shade is obtained with the second coat, apply a third coat of clear TITANLUX Water-based Satin Deco Varnish-Stain, which will not darken the final shade.

Furniture Restoration: Brittle and resinous varnishes (japan, copal), wax, paraffin etc. have to be completely removed beforehand. The more porous and absorbent the wood is, the more its grain is highlighted on applying TITANLUX Water-based Satin Deco Varnish-Stain and the darker it becomes. If you want to tone down contrasts and obtain more uniform softer shades, apply a first coat of clear TITANLUX Water-based Satin Deco Varnish-Stain.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, lightly sand and directly apply the varnish.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

If they are in poor condition or waxed, remove old varnish coats completely and proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2015-07

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

04F - TITANLUX WATER-BASED VARNISH STAIN DECO

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

