

# TITANXYL WATER BASED LASUR COLOUR

Indoor - Outdoor



Product Code: 04M

## Description

It is the ideal treatment for the comprehensive protection of wood,. Water repellent. Quick-drying. High resistance to outdoor conditions and to the destructive action of sun radiation. Transparent intermixable colours which allow to see the natural appearance of wood, enhancing its beauty. Because of its micro-porous structure, it does not form any film on the surface, allowing the passage of water vapour between the inside and outside of the wood and avoiding that the surface cracks or flakes, and thus avoiding sanding.

## Fields of Application

Indoors and Outdoors. For the protection and decoration of windows, doors, beams, banisters and overhangs in wood protection and maintenance of all kinds of wood structures.

## Technical Data

<b>Product Type</b>	Acrylic Alkyd
<b>Finish</b>	Satin
<b>Colour (UNE EN ISO 11664-4)</b>	Clear and colour range
<b>Density (UNE EN ISO 2811-1)</b>	1,01 - 1,06 Kg/l
<b>Coverage (UNE 48282)</b>	12 - 16 m <sup>2</sup> /l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	1 - 2 hours
<b>Recoat time at 23°C 60% RH (UNE 48283)</b>	12 hours
<b>Methods of Application</b>	Brush, roller and spray-gun
<b>Equipment Cleaning</b>	Water
<b>Application Temperature, RH&lt;80%</b>	+10 °C - +30 °C
<b>Volume Solids (UNE EN ISO 3233-3)</b>	21 - 25 %
<b>VOC (UNE EN ISO 11890-2)</b>	2.004/42IIA (e) (150/130) Max. COV 28g/l
<b>Pack sizes</b>	4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Carefully stir in the can. Apply without thinning and following the wood grain. The wood to be treated has to be clean, dry and free of any coat of varnish or paint so as to assist TITANXYL in impregnating them fully.

**Resinous or tropical wood:** Please refer to the Technical Service.

The Clear Lasur, without colour coats below, is only suitable for indoor or outdoor use when not exposed to weathering.

### BARE SURFACES:

**New wood:**If fungicide or insecticide protection is needed, previously apply TITANXYL Protection Total Ultra.

**Indoors:** 2 coats of Water-Based Satin TITANXYL Lasur Colour.

**Outdoors:** One coat of Water-Based TITANXYL Undercoat Ultra and 2 coats of Water-Based Satin TITANXYL Lasur Colour.

**Old unvarnished wood:** It is essential to entirely remove the dried out, greyed surface by sanding or surfacing thoroughly until the wood in good condition is exposed. Then treat like new wood.

**Wood previously treated with lasur:** Remove dust and apply Water-Based Satin TITANXYL Lasur Colour. Deeper shades are obtained if a further coat of the previously used colour is applied. Carry out maintenance when you begin to see bare wood, owing to the self-controlled wear effect of TITANXYL.

#### MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

**Previously varnished wood:** Remove the existing coats entirely with TITAN Plus Paint Stripper and proceed as on new wood,.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2018-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



# TITAN

04M - TITANXYL WATER BASED LASUR COLOUR

#### INDUSTRIAS TITAN S.A.U.

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

