

TITANXYL TECAGEL



Product Code: 04R

Description

Natural oil-based product which impregnates and protects teak wood. Jelly texture that allows easy application. Non-drip. Non-splatter. It contains UV filters. The pigmented gel makes wood outdoors more resistant to greying.

Fields of Application

For the protection and decoration of wood under outdoor conditions. Especially suitable for garden furniture, ipe decking tiles, pergolas, fences, etc.

It does not damage chlorinated rubber joints on boat decks.

Technical Data

Colour (UNE EN ISO 11664-4)	Colorless and honey teak
Density (UNE EN ISO 2811-1)	0.82 - 0.86 Kg/l
Coverage (UNE 48282)	30 - 40 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	2 - 3 hours
Recoat time at 23°C 60% RH (UNE 48283)	24 hours
Methods of Application	Sponge
Equipment Cleaning	TITAN Odourless Thinner or Turpentine.
Volume Solids (UNE EN ISO 3233-3)	28 - 29 %
Pack sizes	750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Oil and grease-stained or aged teak: Clean, degrease with TITAN YATE Rust Remover. Flush with plenty of fresh water. Remove by sanding any remaining trace of dirt or oil, and the greyish outside coat. Wood has to be completely dry before applying TITANXYL Teak Gel.

Apply the gel with the sponge especially provided in the pack. A cleaning cloth can also be used. Spread a thin coat of product. Wait 5 minutes and remove any excess gel with a clean piece of cloth. If wood is very porous, apply a second coat.

Avoid any excess product because this would delay drying and cause dirt retention.

Allow drying for at least 24 hours before walking on the surface, or recoating, if required.

Two coats are recommended for the first time. For maintenance, subsequent retouches every 3 - 5 months will be enough.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2014-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

04R - TITANXYL TECAGEL

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

