

# TITANXYL WATERBASED WOODWORM TREATMENT

Indoor - Outdoor



Product Code: 04Z

## Description

Ready to use. For new and used wood. It protects wood against worms and it is an effective treatment for the previously damaged wood. It kills worms and protects wood against possible future woodworm attacks. Clear, it does not stain wood. easy application, it penetrates into the wood without forming any film. Low odour.

**Health Registry No. 16-80-08183 (Spain).**

## Technical Data

<b>Colour (UNE EN ISO 11664-4)</b>	Clear
<b>Density (UNE EN ISO 2811-1)</b>	1.01 Kg/l
<b>Coverage (UNE 48282)</b>	Preventive action: 200 ml/m <sup>2</sup> , Treatment action: 300 ml/m <sup>2</sup>
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	1 hour
<b>Recoat time at 23°C 60% RH (UNE 48283)</b>	24 hours
<b>Methods of Application</b>	General public: Apply by brush on the wood to be treated. Do not thin / Specialized personnel: Apply on the wood to be treated by brush, roller, spraying or immersion. Do not thin.
<b>Thinner</b>	Ready to use
<b>Equipment Cleaning</b>	Water and soap
<b>Application Temperature, RH&lt;80%</b>	+10°C - +30°C
<b>Pack sizes</b>	4 l (only for professional use) and 750 ml
<b>Composition</b>	Permethrin 0.25%, solvents and excipients q.s. 100%.

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Certificates

It complies with the following standards:

**EN 46-1 Standard:** Determination of the preventive performance against newly hatched larvae of *Hylotrupes bajulus*, through ageing tests by evaporation, according to EN 73 and by half-wash, according to UNE-EN 84.

**UNE-EN 49 Standard:** Determination of the preventive performance against *Anobium punctatum* through ageing test by evaporation, according to EN 73.

**EN 118 Standard:** Determination of the preventive performance against *Reticulitermes* termites, through ageing test by evaporation, according to EN 73.

**UNE-EN 1390 Standard:** Determination of the curative action of a protector against larvae of *Hylotrupes bajulus*.

**EN 370 Standard:** Determination of the curative action against *Anobium punctatum*, together with the ageing tests by evaporation according to EN 73.

## Directions for use

### GENERAL REMARKS:

Ready to use product. Do not thin. Carefully stir the contents in the pack. Tightly close the pack after use.

Before applying TITANXYL Woodworm Waterbased Treatment, protect the plastic items.

The woods to be treated have to be clean, dry and free from any previous coat of varnish or paint in order to achieve their suitable impregnation with TITANXYL Woodworm Waterbased Treatment.

The wood moisture content must not exceed 12% in hard wood and 15% in soft wood.

Wood damaged by woodworm: Apply by injection until saturation, through the holes caused by wood worm or specially pierced holes.

Wood not damaged by woodworm: For a prevention effect, apply by brush or immersion on bare surfaces (free from any varnish or paint).

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Safety interval: 48 hours. It must never be shorter than the time needed for surface drying.

Issue date: 2016-11

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



# TITAN

04Z - TITANXYL WATERBASED WOODWORM TREATMENT

### INDUSTRIAS TITAN S.A.U.

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

