

# TITAN ALKYD PASTE FILLER

Indoor



Product Code: 052

## Description

All purpose, quick drying alkyd paste filler. Excellent product for elimination of unevenness and levelling of surfaces, leaving them smooth and in the best conditions to be painted with alkyd, oil-based and water-based paints and enamels, etc., and also with nitrocellulose paints.

Great adhesion, toughness and excellent spreading rate. Quick drying. Easy sanding.

## Fields of Application

Suitable for any kind of surface such as wood, iron, etc., where a smooth and high quality finish is required.

## Technical Data

<b>Product Type</b>	Synthetic
<b>Finish</b>	Matt
<b>Colour (UNE EN ISO 11664-4)</b>	White, grey and white for wood. (White filler for wood is softer and it allows dry sanding).
<b>Density (UNE EN ISO 2811-1)</b>	1.96 - 2.04 Kg/l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	4 - 6 hours
<b>Methods of Application</b>	Brush and putty-knife
<b>Equipment Cleaning</b>	TITAN Turpentine or Synthetic and Grease Thinner
<b>Volume Solids (UNE EN ISO 3233-3)</b>	68 - 71%
<b>VOC (UNE EN ISO 11890-2)</b>	2.004/42IIA (g) (450/350) Max. COV 250 g/l
<b>Pack sizes</b>	375 ml and 125 ml.

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Remove any loose or poorly adhered particles on the surface. Spread the product on the surface. Smooth up. Once dry, sand for levelling up. Let to dry and paint.

After having applied the filler, wait at least 6 - 8 hours before recoating with the paint or topcoat enamel. Previously smooth up or sand the surface.

It can also be used as an intermediate coat between alkyd primer coats and topcoats based on strong solvents. They can be both 1 or 2 component topcoats. The filler intermediate coat will prevent the lower coats from wrinkling.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2015-04

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

**TITAN**

052 - TITAN ALKYD PASTE FILLER

**INDUSTRIAS TITAN S.A.U.**

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

