

# HIDROLIN

Water-Based Fixative. Indoor - Outdoor



Product Code: 056



## Description

Water-based fixative sealer, with high penetrating performance. For indoor and outdoor use. To prime surfaces before painting them and ensure a right application of the paint topcoats.

## Fields of Application

Especially suitable for:

Unsound or highly porous walls and ceilings made out of plaster, concrete or brick.

To seal or reinforce old paints before recoating.

Also used as a colourless protector for mortar and old surfaces, which are not to be painted but where more consistency is required in order to prevent damage.

## Technical Data

Product Type	Acrylic styrene
Colour (UNE EN ISO 11664-4)	Clear
Density (UNE EN ISO 2811-1)	1.00 - 1.10 Kg/l
Coverage	8 - 12 m <sup>2</sup> /l
Drying at 23°C 60 % RH (UNE 48301)	20 - 30 minutes
Recoat time at 23°C 60% RH (UNE 48283)	4 - 6 hours
Methods of Application	Brush, roller and spray-gun
Thinning	Water
Equipment Cleaning	Water
Application Temperature, RH<80%	+10 °C - +30 °C. Do not apply if rain is foreseen in the next hours
Flash Point (UNE EN ISO 3679)	Non flammable
Volume Solids (UNE EN ISO 3233-3)	12 - 13 %
VOC (UNE EN ISO 11890-2)	2004/42/IIA (g) (50/30) Max. COV 5 g/l
Pack sizes	4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Carefully stir the contents in the pack.

Clean the surfaces to be painted. Remove dust or poorly adhered paints.

Apply a single coat by brush or by roller. Spread HIDROLIN Fixative on the surface up to complete absorption.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona  
(Espanya)  
Teléfono 934 842 500  
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210  
N.I.F. B-08218158

