

TITAN WATER-BASED CRACK FILLER



Product Code: 05A

Description

Water-based ready-to-use filler to be applied indoors. For plaster, concrete, wood, masonry. Easy to apply. Non shrink. Non cracking.

Technical Data

| | |
|---|---|
| Finish | Matt |
| Colour (UNE EN ISO 11664-4) | White |
| Density (UNE EN ISO 2811-1) | 1.90 - 2.00 Kg/l |
| Drying at 23°C 60 % RH (UNE 48301) | 20 - 60 minutes |
| Recoat time at 23°C 60% RH (UNE 48283) | 6 - 8 hours |
| Methods of Application | Putty knife and trowel. |
| Equipment Cleaning | Water |
| Tinting | TITAN Universal Tinting Colours or Professional Water Based Due |
| Volume Solids (UNE EN ISO 3233-3) | 62 - 63 % |
| VOC (UNE EN ISO 11890-2) | 2.004/42IIA (g) (50/30) Max. COV 0 g/l |
| Pack sizes | 4 l, 750 and 250 ml. |

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Remove any loose or unsound material on the surface. Spread the product on the surface and smooth up. Once dry, sand for levelling and paint. For cracks or very absorbent surfaces, moist or prime with Hidrolin Fixative before applying the filler. If applying on metal surface, previously protect them with the suitable primers.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2016-04

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

05A - TITAN WATER-BASED CRACK FILLER

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

