

TITAN SYNTHETIC PRIMER

Indoors



Product Code: 060

Description

Quick-drying synthetic primer for iron. It ensures perfect adherence of the top coats (bonds or fillers and paints).

Fields of Application

Very suitable for heating radiators and machinery indoors.

Technical Data

Product Type	Alkyd
Finish	Matt
Colour (UNE EN ISO 11664-4)	White, grey and red
Density (UNE EN ISO 2811-1)	1.50 - 1.62 Kg./l
Coverage	13 - 16 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	4 - 6 hours
Recoat time at 23°C 60% RH (UNE 48283)	18 - 24 hours
Methods of Application	Brush
Equipment Cleaning	TITAN Synthetics and Grease Thinner or Turpentine
Application Temperature, RH<80%	+10 °C - +30 °C
Flash Point (UNE EN ISO 3679)	39 °C
Volume Solids (UNE EN ISO 3233-3)	57 - 62 %
VOC (UNE EN ISO 11890-2)	2.004/42IIA (g) (450/350) Max. COV 330 g/l
Pack sizes	4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Stir well in the pack before using. The surfaces to be primed have to be clean and dry, as well as free from grease and rust. For outdoor works, exposed to weathering, it is necessary to apply a suitable anticorrosive protection, such as TITANLUX Rust Preventive Primer or Multi Purpose Primer.

BARE SURFACES:

Directly apply 1 or 2 coats of TITAN Primer.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Completely remove all previous coats and proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

