

TITANLUX SYNTHETIC RUST PREVENTIVE PRIMER

Indoors- Outdoors



Product Code: 062

Description

Quick-drying alkyd primer for iron. Great adhesion, hardness and resistance to outdoor conditions.

Fields of Application

Indoor and outdoor use. Rust-preventive protection of iron in furniture, machinery, electrical household appliances and electric boxes.

Technical Data

Product Type	Modified alkyd
Finish	Satin
Colour (UNE EN ISO 11664-4)	Orange and Grey
Density (UNE EN ISO 2811-1)	1.35 - 1.40 Kg/l
Coverage	10 - 14 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	1 - 2 hours
Recoat time at 23°C 60% RH (UNE 48283)	8 hours
Methods of Application	Brush
Equipment Cleaning	Synthetics Thinner or White Spirit
Application Temperature, RH<80%	+10°C - +30°C
Flash Point (UNE EN ISO 3679)	40 °C
Volume Solids (UNE EN ISO 3233-3)	52,8 - 59 % (depending on colour)
VOC (UNE EN ISO 11890-2)	2004/42IIA (i) (600/500) Max. COV 370 g/l
Pack sizes	4 l , 750 ml, 375 ml and 125 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Stir well before using.

The surfaces to be primed have to be clean and dry, as well as free from grease and rust.

When finishing with products based on strong solvents such as nitrocellulose, vinyl and epoxy, it is necessary to apply an intermediate coat of TITAN Alkyd Paste Filler

BARE SURFACES:

Directly apply two coats of TITANLUX Rust Preventive Primer

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Thoroughly remove old paint coats and proceed as for non prepared surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products



Akzo Nobel Coatings, S.L.U – Carrer Felixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(España)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F. 95, H. nº B-45052, Inscrip. 210
N.I.F. B-08218158

