

# TITAN SINGLE COAT

Indoor. Matt



Product Code: 069

## Description

Wash-resistant, matt emulsion paint for decorating indoor walls and ceilings. High covering. Snow white. Non-drip, non-splatter. **In most cases, only a single coat is required.**

## Technical Data

<b>Product Type</b>	Emulsion copolymer
<b>Finish</b>	Matt
<b>Colour (UNE EN ISO 11664-4)</b>	White and colour range
<b>Density (UNE EN ISO 2811-1)</b>	White: 1.56 - 1.60 Kg/l / Colours: 1.39 - 1.60 Kg/l
<b>Coverage (UNE 48282)</b>	9 - 11 m <sup>2</sup> /l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	20 - 60 minutes
<b>Recoat time at 23°C 60% RH (UNE 48283)</b>	6 - 8 hours
<b>Methods of Application</b>	Brush, roller and spray-gun
<b>Thinner</b>	Water
<b>Equipment Cleaning</b>	+10°C - +30°C
<b>Tinting</b>	TITAN Universal Tinting Colours, Professional Water-based Dye and Servicolor System
<b>Volume Solids (UNE EN ISO 3233-3)</b>	White: 41.5 - 42.5 %, Colours: 40 - 47 %
<b>VOC (UNE EN ISO 11890-2)</b>	2004/42/IIA (a) (75/30) Max. COV 15g/l
<b>Pack sizes</b>	White and light shades (depending on colour): 10 l, 5 l (rectangular bucket) and 750 ml. Deep shades (depending on colour): 5 l (rectangular bucket) , 2,5 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Certificates

Wet-Scrub Resistance, UNE EN ISO 11998: Class 2

## Directions for use

### GENERAL REMARKS:

Carefully stir the contents in the pack. The surfaces to be painted have to be clean, dry and sound.

### BARE SURFACES:

Apply a first coat thinned with 10 - 15% water. Apply a second unthinned coat.

If the surfaces are in poor condition, repair all the damaged areas, remove all poorly adhered particles and material. Clean all existing dirt and dust.

In order to homogenise porosity and improve the finish, as well as on distemper and size paints, whitewash or the surfaces where these have been removed, it is recommended to apply a first coat of TITAN Sealing Primer or Hidrolin Fixative.

**MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:**

Directly apply the paint after previous washing or brushing. Do not thin.

**MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:**

Thoroughly remove old paint coats and proceed as for non prepared surfaces.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2015-06

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



# TITAN

069 - TITAN SINGLE COAT

**INDUSTRIAS TITAN S.A.U.**

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

