

TITAN SINGLE COAT

Indoor. Matt



Product Code: 069



Description

Wash-resistant, matt emulsion paint for decorating indoor walls and ceilings. High covering. Snow white. Non-drip, non-splatter. **In most cases, only a single coat is required.**

Technical Data

Product Type	Emulsion copolymer
Finish	Matt
Colour (UNE EN ISO 11664-4)	White and colour range
Density (UNE EN ISO 2811-1)	White: 1.54 - 1.60 Kg/l / Colours: 1.39 - 1.60 Kg/l
Coverage	9 - 11 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	20 - 60 minutes
Recoat time at 23°C 60% RH (UNE 48283)	6 - 8 hours
Methods of Application	Brush, roller and spray-gun
Thinner	Water
Equipment Cleaning	+10°C - +30°C
Tinting	TITAN Universal Tinting Colours, Professional Water-based Dye and Servicolor System
Volume Solids (UNE EN ISO 3233-3)	White: 41.5 - 42.5 %, Colours: 40 - 47 %
VOC (UNE EN ISO 11890-2)	2004/42/IIA (a) (75/30) Max. COV 15g/l
Pack sizes	White and light shades (depending on colour): 10 l, 5 l (rectangular bucket) and 750 ml. Deep shades (depending on colour): 5 l (rectangular bucket) , 2,5 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Certificates

Wet-Scrub Resistance, UNE EN ISO 11998: Class 2
VOC Emission ISO 16000-6: A +

Directions for use

GENERAL REMARKS:

Carefully stir the contents in the pack. The surfaces to be painted have to be clean, dry and sound.

BARE SURFACES:

Apply a first coat thinned with 10 - 15% water. Apply a second unthinned coat.

If the surfaces are in poor condition, repair all the damaged areas, remove all poorly adhered particles and material. Clean all

existing dirt and dust.

In order to homogenise porosity and improve the finish, as well as on distemper and size paints, whitewash or the surfaces where these have been removed, it is recommended to apply a first coat of TITAN Sealing Primer or Hidrolin Fixative.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Directly apply the paint after previous washing or brushing. Do not thin.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Thoroughly remove old paint coats and proceed as for non prepared surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2021-10

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products



Akzo Nobel Coatings, S.L.U – Carrer Felixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(España)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F. 95, H. nº B-45052, Inscrip. 210
N.I.F. B-08218158

