

# WATER-BASED PAINT STRIPPER FOR ANTIFOULINGS

## TITAN



**Product Code:** 06G

## Description

Special paint stripper for easily and quickly removing antifouling paints on surfaces which were suitably primed with epoxy primers.

Only for professional use.

## Fields of Application

Water-based paint stripper for easily and quickly removing old antifouling paint coats. Especially suitable for polyester hulls because it does not damage the gel-coat.

## Technical Data

<b>Coverage</b>	3 - 5 m <sup>2</sup> /l
<b>Methods of Application</b>	Brush and roller
<b>Thinner</b>	Water
<b>Pack sizes</b>	4 l

## Directions for use

### GENERAL REMARKS:

Apply a thick coat and wait for 4 - 5 hours approximately. Apply a second coat and allow the paint stripper to soften old antifouling coats for 12 - 18 hours. Wash with water jet until all old coats get stripped off. If necessary, repeat this same procedure again.

Protect the gel-coat of non-submerged surfaces, because the paint stripper can decrease its gloss (It does not act on enamels and two component primers).

Do not use this product on areas where there can be unprimed metal

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2016-01

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona  
(Espanya)  
Teléfono 934 842 500  
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210  
N.I.F. B-08218158

