

# TEAK OIL

## TITAN



**Product Code:** 07B

## Description

Natural oil-based and transparent iron oxides product which soaks and protects teak wood. It contains UV filters Very low odour.

## Fields of Application

For protection and restoration of teak under outdoor conditions.

## Technical Data

<b>Colour (UNE EN ISO 11664-4)</b>	Clear and teak
<b>Density (UNE EN ISO 2811-1)</b>	0.80 - 0.85 Kg/l
<b>Coverage</b>	10 - 18 m <sup>2</sup> /l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	2 - 4 hours
<b>Recoat time at 23°C 60% RH (UNE 48283)</b>	24 hours
<b>Methods of Application</b>	Brush or cotton pad
<b>Equipment Cleaning</b>	Odourless Thinner or White Spirit.
<b>Volume Solids (UNE EN ISO 3233-3)</b>	27 - 28 %
<b>Pack sizes</b>	4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Oil and grease-stained or aged teak: Clean and degrease with TITAN YATE Rust Remover and flush with fresh water. Remove by sanding any remaining trace of dirt or oil, and the greyish outside coat. Wood has to be completely dry before applying TITAN YATE Teak Oil.

Allow drying for at least 24 hours before walking on the surface, or recoating, if required.

Two coats are recommended for the first time. For maintenance, subsequent retouches every 3 - 5 months will be enough.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona  
(Espanya)  
Teléfono 934 842 500  
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210  
N.I.F. B-08218158

