

RED LEAD

Indoors - Outdoors.

TITAN



Product Code: 07F

Description

Rust-preventive oil-based primer for iron and steel. Being a greasy primer, it reaches and impregnates the areas where it is difficult to remove rust, ensuring a very effective protection. Special for fishing boats and highly corrosive marine environments.

Fields of Application

For any kind of iron and steel structures. It is also intended as a primer for wooden boats.

Technical Data

Product Type	Oleo-synthetic
Finish	Semi matt
Colour (UNE EN ISO 11664-4)	Typical orange
Density (UNE EN ISO 2811-1)	1.96 - 2.02 Kg/l
Coverage (UNE 48282)	10 - 14 m ² /l (35 - 45 dry μ)
Drying at 23°C 60 % RH (UNE 48301)	6 - 8 hours.
Recoat time at 23°C 60% RH (UNE 48283)	48 - 72 hours.
Methods of Application	Brush
Equipment Cleaning	TITAN Synthetics and Grease Thinner or Turpentine.
Recommended Thickness (UNE EN ISO 2808)	70 - 100 μ
Flash Point (UNE EN ISO 3679)	44 °C
Volume Solids (UNE EN ISO 3233-3)	56 - 57 %
VOC (UNE EN ISO 11890-2)	2004/42IIA (i) (600/500) Max. VOC 350 g/l
Pack sizes	4 l and 750 ml.

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Carefully stir the contents in the can before use. The surfaces have to be clean and dry as well as free from grease and rust. Apply two thin coats. Let to thoroughly dry and apply the finishing paint. If a quicker drying is required, use TITAN YATE Marine Primer.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management:

Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points.

Calculate the amount of product you will need to avoid waste and extra costs.

Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-08

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

07F - RED LEAD

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

