

MULTI-PURPOSE RUST REMOVER

TITAN

Product Code: 07U

Description

Excellent rust remover, polishing, degreasing, anti-calcareous and general purpose cleaning agent, for wood, iron, metal, chrome-plating. etc.

Technical Data

| | |
|-----------------------------|--|
| Density (UNE EN ISO 2811-1) | 1.25 - 1.30 Kg/l |
| Pack sizes | 1 l and 250 ml. 5 l only for professional use. |

Directions for use

GENERAL REMARKS:

Iron, aluminium, zinc-plated iron: Apply the product on the affected area by means of a brush or spray. Let the product until the stain would disappear. Afterwards rinse with water. On aluminium and zinc-plated iron, it improves the bondage of primers and finishing products.

Wood: It cleans and de-greases teak, iroko and all other kinds of wood. Thin the product with 50% water and spread it on wood, allowing it to act. Once clean, rinse with water. The mixing rate may vary, depending on the wood dirt.

Polyester with rust stains: Apply on the rust-stained polyester until the stain disappears. Wash with plenty of fresh water.

Concrete and polyester swimming pools: Useful for cleaning concrete and polyester painted swimming pools, because it acts as a degreasing and lime removing agent.

Cleaner and polisher: Because of its special characteristics, this product can be used for removing rust, lime etc. from stainless steel, chrome-plated, vitrified taps and sinks, boat propellers. etc.

Highly suitable for cleaning bathtubs which are to be overcoated with the TITAN YATE Epoxy Primer plus Polyurethane + Acrylic or Ceramic Finish Enamel.

Avoid spilling product on marble and tessellated pavement.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2020-06

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona (Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

