

# THINNER FOR TITAN SWIMMING POOL PAINTS

Solvent-Based



Product Code: 083

## Description

Mixture of aromatic hydrocarbons and esters. Medium evaporation speed.

## Fields of Application

For thinning TITAN SIRENA Solvent-Based Swimming Pool Paint and TITAN Chlorinated Rubber Paint for Swimming Pools. Thinning rate must not exceed 5 - 10%. Easy application by roller.

Also suitable for application by roller of quick-drying enamels (Hammered or Smooth OXIRON and chlorinated rubber).

## Technical Data

Density (UNE EN ISO 2811-1)	0.86 - 0.88 Kg/l
Flash Point (UNE EN ISO 3679)	32 °C
Pack sizes	1 l

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-11

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



# TITAN

083 - THINNER FOR TITAN SWIMMING POOL PAINTS

**INDUSTRIAS TITAN S.A.U.**  
España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94  
Portugal: Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

