

BLANCDUR

Stain-Hiding Isolating Paint. Indoors. Matt



Product Code: 088

Description

Isolating stain-hiding high covering paint (one single coat) with excellent adhesion and whiteness. Non-yellowing. Alkali resistant. Odourless (free from aromatic solvents).

Fields of Application

Appropriate for ceilings and walls of bath-rooms, kitchens, workshops, hotels and hospitals due to its great isolating power against smoke, vapour and grease dark stains.

Technical Data

Product Type	Acrylic copolymer
Finish	Matt
Colour (UNE EN ISO 11664-4)	White
Density (UNE EN ISO 2811-1)	1.53 - 1.59 Kg/l
Coverage (UNE 48282)	4 - 6 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	2 - 3 hours
Methods of Application	Brush and Roller
Equipment Cleaning	Odourless Thinner or White Spirit
Application Temperature, RH<80%	+10 °C - +30 °C
Flash Point (UNE EN ISO 3679)	62 °C
Volume Solids (UNE EN ISO 3233-3)	61 - 62 %
VOC (UNE EN ISO 11890-2)	2.004/42IIA (i) (600/500) Max COV 400 g/l
Pack sizes	4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Stir well before using. Do not thin. The surfaces to be painted have to be clean, dry and suitably primed. There is no need to thoroughly remove any rest of dirt or grease. Excellent adhesion, with just a minimum surface preparation, even on previous low quality emulsion paint. If a second coat is needed, let to dry for 8 hours at least.

BARE SURFACES:

Directly apply Blancdur.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Directly apply Blancdur.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Completely remove loose or poorly adhered material, all previous paint coats etc., and directly apply.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2018-09

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

088 - BLANCDUR

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

