

# BLANCDUR

**Stain-Hiding Isolating Paint. Indoors. Matt**



**Product Code:** 088

## Description

Isolating stain-hiding high covering paint (one single coat) with excellent adhesion and whiteness. Non-yellowing. Alkali resistant. Odourless (free from aromatic solvents).

## Fields of Application

Appropriate for ceilings and walls of bath-rooms, kitchens, workshops, hotels and hospitals due to its great isolating power against smoke, vapour and grease dark stains.

## Technical Data

<b>Product Type</b>	Acrylic copolymer
<b>Finish</b>	Matt
<b>Colour (UNE EN ISO 11664-4)</b>	White
<b>Density (UNE EN ISO 2811-1)</b>	1.53 - 1.59 Kg/l
<b>Coverage</b>	4 - 6 m <sup>2</sup> /l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	2 - 3 hours
<b>Methods of Application</b>	Brush and Roller
<b>Equipment Cleaning</b>	Odourless Thinner or White Spirit
<b>Application Temperature, RH&lt;80%</b>	+10 °C - +30 °C
<b>Flash Point (UNE EN ISO 3679)</b>	62 °C
<b>Volume Solids (UNE EN ISO 3233-3)</b>	61 - 62 %
<b>VOC (UNE EN ISO 11890-2)</b>	2.004/42IIA (i) (600/500) Max COV 400 g/l
<b>Pack sizes</b>	4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Stir well before using. Do not thin. The surfaces to be painted have to be clean, dry and suitably primed. There is no need to thoroughly remove any rest of dirt or grease. Excellent adhesion, with just a minimum surface preparation, even on previous low quality emulsion paint. If a second coat is needed, let to dry for 8 hours at least.

### BARE SURFACES:

Directly apply Blancdur.

### MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Directly apply Blancdur.

### MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Completely remove loose or poorly adhered material, all previous paint coats etc., and directly apply.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2018-09

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona  
(Espanya)  
Teléfono 934 842 500  
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210  
N.I.F. B-08218158

