# TITAN UNIVERSAL TINTING COLOURS







## Description

Universal tinting colours for paints. High concentration and compatibility. A previous test is recommended.

## Fields of Application

To tint synthetic and greasy paints and varnishes, as well as coatings made out of chlorinated rubber, nitrocellulose and epoxy resins. It is also suitable for water-emulsion, size and distemper paints. Moreover, it can tint non-structural concrete.

## **Technical Data**

Colour (UNE EN ISO 11664-4)	Colour range
Density (UNE EN ISO 2811-1)	1.16 - 1,97 Kg/l
Pack sizes	250 ml, 100 ml and 50 ml.

## Directions for use

#### **GENERAL REMARKS:**

Shake well before use. Maximum amount of mixture: 5% in volume. Do not use this product directly, without adding it to paints. Mix the tint and the base paint or varnish, if possible by means of a mechanical shaker.

#### **Precautions**

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



