

ODOURLESS THINNER



Product Code: 08S

Description

Mixture of paraffinic hydrocarbons and glycol esters. Slow evaporation thinner.

Fields of Application

For thinning oil-based and synthetic paints and varnishes when very low odour is required. Suitable for equipment cleaning.

Technical Data

Colour (UNE EN ISO 11664-4)	Colourless
Density (UNE EN ISO 2811-1)	0.77 - 0.79 Kg/l
Flash Point (UNE EN ISO 3679)	45º C.
Pack sizes	5 l, 1 l and 500 ml

Directions for use

GENERAL REMARKS:

In applications by spray gun, the recommended thinning rate is 15% to 25%. In applications by brush the recommended thinning rate is 5%.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2014-09

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

08S - ODOURLESS THINNER

INDUSTRIAS TITAN S.A.U.
España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94
Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

