

# TITAN UNIVERSAL THINNER



**Product Code:** 08U



## Description

Mixture of a wide range of solvents. Quick evaporation and high thinning power.

## Fields of Application

Suitable for thinning most paints, enamels, varnishes, lacquers and primers.

## Technical Data

<b>Colour (UNE EN ISO 11664-4)</b>	Colourless
<b>Density (UNE EN ISO 2811-1)</b>	0.83 - 0.86 Kg/l
<b>Flash Point (UNE EN ISO 3679)</b>	7 °C
<b>Pack sizes</b>	20 l, 5 l, 1 l, 500 ml and 250 ml

## Directions for use

### GENERAL REMARKS:

In applications by spray gun, the recommended thinning rate is 15% to 25%. Not recommended for applications by brush.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

**Waste management:** Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2019-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona (Espanya)  
Teléfono 934 842 500  
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210  
N.I.F. B-08218158



08U - TITAN UNIVERSAL THINNER