

# DUTCH VARNISH



**Product Code:** 091 0012

## Description

Fat varnish-medium to be mixed with oil colours. Also as a final varnish. It improves drying, colour brightness, gloss and transparency. It prevents cracking. If used as a final varnish, thinning is recommended.

## Fields of Application

Mixed with oil colours, it gives them more vividness, better drying properties, solidity, flexibility and gloss, and makes it possible to obtain high transparency effects. It prevents cracking.

Thinned with turpentine oil or petroleum spirit, it is used as a final varnish for pictures-. It produced high quality finishes, which are similar to the traditional Flemish pictures.

It can be applied between colour coats to achieve better adhesion (restoring).

If required, it is possible to add a small amount of cobalt drier so that it can dry a little more quickly.

## Technical Data

<b>Finish</b>	Reddish transparent liquid. Gloss
<b>Density (UNE EN ISO 2811-1)</b>	0.83 - 0.89 Kg/l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	1 - 1:30 hours
<b>Methods of Application</b>	Brush or flat brush
<b>Thinner</b>	Turpentine oil or petroleum spirit (white spirit)
<b>Equipment Cleaning</b>	Brush Cleaner
<b>Flash Point (UNE EN ISO 3679)</b>	41 °C
<b>Pack sizes</b>	1 l, 250 ml and 100 ml.

## Directions for use

### GENERAL REMARKS:

Previously shake the product in the bottle.

As a final varnish, apply it diluted and by thin coats on thoroughly dry colours.

To be mixed with oil colours in the suitable rate, depending on requirements. It is completely soluble. The more varnish it is added to the oil colour, the more transparency, gloss and drying power will be obtained.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2014-11

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

**TITAN**

091 0012 - DUTCH VARNISH

**INDUSTRIAS TITAN S.A.U.**

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

