

# TURPENTINE OIL



Product Code: 091 0031



## Description

Very volatile thinner for oil colours, varnishes and driers. It evaporates without leaving any residue.

## Fields of Application

Ideal to apply first coats (thin). It enhances the application of oil colours and stimulates their drying, without leaving any residue.

Suitable to obtain a variety of effects such as veiling, transparencies, especially in backgrounds. If used in excessive amounts to thin oil colours, it may cause crackling, splitting, or shadows produced by porosity differences, etc., especially in the topmost layers of the work.

It can also be used for equipment cleaning

## Technical Data

<b>Colour (UNE EN ISO 11664-4)</b>	Colourless
<b>Density (UNE EN ISO 2811-1)</b>	0.86 - 0.88 Kg/l
<b>Flash Point (UNE EN ISO 3679)</b>	32 - 46 °C
<b>Pack sizes</b>	1 l, 250 ml and 100 ml

## Directions for use

### GENERAL REMARKS:

Thoroughly mix the oil colour and the turpentine oil, to obtain the suitable fluidity for the work to be performed.

Because of its good thinning power, a wide variety of mixing rates can be possible, always depending on the judgement and requirements of the user.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2014-07

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



**TITAN**

091 0031 - TURPENTINE OIL

**INDUSTRIAS TITAN S.A.U.**

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

