

TITAN SHELLAC



Product Code: 091 0045



Description

Gloss natural lacquer. For isolating and priming porous surfaces.

Fields of Application

It is used as a topcoat for gold leaf, silver leaf and alike. It is an excellent hard and gloss finishing varnish for acrylic and/or vinyl paints. It can be used as a primer for porous surfaces, such as plaster or wood. It avoids excessive absorption. It dries by evaporation. If dyes are added to alcohol, a wide variety of transparent shades can be obtained. Commonly used for polychrome finishes.

Technical Data

Finish	Transparent ambarine liquid. Gloss.
Density (UNE EN ISO 2811-1)	0.86 - 0.88 Kg/l
Drying at 23°C 60 % RH (UNE 48301)	40 - 50 min.
Methods of Application	Brush, flat brush or cotton pad
Thinner	Alcohol
Equipment Cleaning	Alcohol or Brush cleaner.
Flash Point (UNE EN ISO 3679)	14 °C
Pack sizes	1 l, 250 ml and 100 ml

Directions for use

GENERAL REMARKS:

On plaster or other porous surfaces, it acts as a primer, applying one or two coats. It can also be used as a gloss finish varnish. On wood: If the wood is new, it has to be smooth (sanded), clean and dry. Then apply 3 or 4 coats with a paintbrush, brush or palette. Let to thoroughly dry between every two coats

On wood, it can also be applied by cotton pad,. Slowly soak and polish according to the classical technique. Avoid excess product. As many coats as required can be applied. Let to thoroughly dry between every two coats until obtaining a uniform and gloss finish.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2014-11

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

091 0045 - TITAN SHELLAC

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764



