

GLOSS ACRYLIC GEL



Product Code: 091 0062

Description

The Gels for acrylics provide a large number of application possibilities for this technique. Mixed with the colour, the transparency, opacity, gloss grade, viscosity or even the texture of the colour are modified.

The Gloss Acrylic Gel has a viscosity which is similar to that of the Extra Fine TITAN Acrylics. One dry, it is gloss, clear, waterproof and elastic.

Fields of Application

Suitable for porous surfaces. It can be applied on any kind of canvas or surfaces made out of wood, concrete, carton, plaster, etc.

It can also be used as base coat or as a top coat for acrylic paints. It increases the coverage of acrylic colours. Because of its adhesive power, it is suitable for collage techniques.

It can overpainted with acrylics, oil colours, etc.

Technical Data

Finish	Gloss
Density (UNE EN ISO 2811-1)	1.03 - 1.05 Kg/l
Drying at 23°C 60 % RH (UNE 48301)	30 - 60 minutes (for a wet thickness of 0.2 - 0.5 mm)
Methods of Application	Flat brush or spatula
Equipment Cleaning	Water
Pack sizes	230 ml and 500 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Thoroughly homogenize the contents in the pack. To be applied on degreased, clean, dry and suitably primed surfaces.

Once mixed with TITAN Acrylics, apply a coat with a maximum thickness of 5 mm, with the aid of a paintbrush, spatula or any other suitable tool. Coats with a thickness exceeding 5 mm are not recommended since they can damage the paint coat.

BARE SURFACES:

Canvas: Gesso Universal Primer.

Plaster or wood: TITAN Sealing Primer or Gesso Universal Primer.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, lightly sand and directly apply.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Thoroughly remove old coats and proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2015-02

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

091 0062 - GLOSS ACRYLIC GEL

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

