

# MODELING PASTE



**Product Code:** 091 0065



## Description

Primer for creating surfaces with volume and textured reliefs. It is to be applied on porous surfaces. It can be overpainted with oil colours and acrylic colours. Once dry, it is white, opaque and hard. It can also be sanded and sculpted.

## Fields of Application

It can be applied on any kind of canvas or on surfaces made out of wood, concrete, carton, plaster, etc. For obtaining more elasticity, it can be mixed with acrylic gels.

## Technical Data

<b>Finish</b>	Matt
<b>Density (UNE EN ISO 2811-1)</b>	1.40 - 1.42 Kg/l
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	30 - 60 minutes (for a wet thickness of 0.2 - 0,5 mm)
<b>Methods of Application</b>	Flat brush or spatula
<b>Equipment Cleaning</b>	Water
<b>Pack sizes</b>	230 ml and 500 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Thoroughly homogenize the contents in the pot and apply by thin coats over surfaces which have to be degreased, clean dry and suitably prepared. It can be dyed with acrylic colours.

### BARE SURFACES:

Canvas: Gesso Universal Primer.

Plaster or wood: TITAN Sealing Primer or Gesso Universal Primer.

### MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, lightly sand and directly apply.

### MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Thoroughly remove old coats and proceed as for bare surfaces.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2015-02

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

**TITAN**

091 0065 - MODELING PASTE

**INDUSTRIAS TITAN S.A.U.**

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

