

CHALK WAX

Colourless



Product Code: 091 0304

Description

Transparent and colourless creamy wax. It fixes and protects the applied paint. It provides a pleasant touch, as well as a unique handicraft looking finish.

Technical Data

Product Type	Wax
Colour (UNE EN ISO 11664-4)	Colourless
Density (UNE EN ISO 2811-1)	0.74 - 0.78 Kg/l
Coverage (UNE 48282)	15 - 25 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	2 - 3 hours
Methods of Application	Rag, brush, cotton pad
Thinner	TITAN White Spirit or TITAN Petroleum Spirit
Flash Point (UNE EN ISO 3679)	>55 °C
Volume Solids (UNE EN ISO 3233-3)	22 - 25 %
Pack sizes	750ml and 250 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Surfaces have to be clean and dry.

It is applied by brush with a rag. Let to dry for 2 - 3 hours and polish until obtaining the required gloss. It can also be used between two colour coats, to achieve certain stripping effects.

Mixed with TITAN Mineral Pitch, it becomes a patina wax for aged looks.

In view of the wide variety of surfaces and available techniques, it is always advisable to perform a test before application.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Issue date: 2016-07

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

091 0304 - CHALK WAX

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

