

GOYA OIL COLOURS



Product Code: 093

Description

Oil colours of exceptional colour vividness. Optimum pigment concentration. Good light fastness. Absolute stability

Fields of Application

Special for application on linen, cotton or other kinds of canvas, suitably primed.

It can also be applied on other surfaces such as wood, tablex, cardboard, etc. provided they are waterproofed with a suitable primer and they have good adhesion.

Technical Data

Finish	Satin-gloss
Colour (UNE EN ISO 11664-4)	Colour card showing a choice of 40 shades
Density (UNE EN ISO 2811-1)	1.10 to 2.45 kg/l (depending on colour)
Drying at 23°C 60 % RH (UNE 48301)	Superficial:1-15 days (depending on the pigment). Drying times are given for an applied layer with a thickness of approximately 0.1 to 0.5 mm.
Methods of Application	By brush, flat brush or spatula.
Thinner	Turpentine oil, petroleum spirit, universal oil and purified linseed oil.
Equipment Cleaning	TITAN Codi Cleaner.
Pack sizes	In tubes containing 20 ml and 60 ml White: 20 ml, 60 ml and 150 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Application : Preferably apply by thin coats.

Surface preparation : The surfaces have to be clean, dry and suitably primed. The primer has to be thoroughly dry before applying the oil colours. Otherwise, cracks might appear as oil colours progressively dry.

On canvas or fabric : GESSO TITAN Universal Primer.

On wood, tablex, cardboard or alike: GESSO TITAN Universal Primer or TITAN Sealing Primer.

Overpainting : They can be overpainted, bearing in mind to apply FINE over THICK to avoid cracking and unwished porosity differences.

FINE has to be understood as : low oil content, thin, fluid

THICK has to be understood as: thick (oily), viscous.

Always keep the works indoors.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2014-06

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

093 - GOYA OIL COLOURS

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

