

EXTRA FINE TITAN ACRYLIC COLOUR



Product Code: 095



Description

Unaltered, opaque or semitransparent colours, depending on the tonality. Solid at light, no yellowing and very flexible. Perfect adherence on any type of surface, previously prepared and free of grease. When applied with the correct method, watercolour effects can be achieved, as well as Gouache, oil painting, etc. with transparencies and other special effects.

Fields of Application

In general, acrylic colours are used for paintings on linen, cotton or other types of canvases, but they can also be applied on any surface that has been previously prepared, with the grease removed.

Technical Data

Product Type	Acrylic
Finish	Satin
Colour (UNE EN ISO 11664-4)	58 shade range
Density (UNE EN ISO 2811-1)	1.10-1.43 Kg/l (depending on the colour).
Drying at 23°C 60 % RH (UNE 48301)	30 minutes
Methods of Application	A paintbrush or spatula
Thinner	Water
Equipment Cleaning	Water
Pack sizes	Tubes: 60ml, Bottles: 250ml, Container: 500 ml (depending on the colour)

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

On clean surfaces, dry and free of grease and primed adequately.

If you wish to delay the drying time, about 5-10 minutes, add 5% of Drying Retarder ACRYLIC TITAN.

BARE SURFACES:

Canvas: apply one or two coats of TITAN Gesso Universal Primer.

Gypsum or wood: apply a generous coat of TITAN sealant or Gesso TITAN.

Other unpainted surfaces: Seek advice

Method of application: Apply a coat with a maximum thickness of 5 mm, with the aid of a paintbrush, spatula or a different utensil. Thicknesses above 5 mm are not recommended since they can damage the paint coat.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2014-06

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

095 - EXTRA FINE TITAN ACRYLIC COLOUR

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

