

ACUALUX TITAN

Indoors - Outdoors. Matt



Product Code: 099



Description

Multiadhesion acrylic paint. Direct use on wood, cardboard, plaster, copper, brass, fibre cement, brick, methacrylate, expanded polystyrene, primed steel, etc. Easy application and levelling. High resistance to washes and abrasion. Writing Board Effect for soft chalk. Crackling effect colours by using Acualux Crackling Medium.

Fields of Application

Suitable for handicrafts on wood, linen, paper, concrete, stone, bisque, clay, plaster, etc.

Technical Data

Finish	Matt
Colour (UNE EN ISO 11664-4)	Range of 41 shades
Density (UNE EN ISO 2811-1)	1.16 to 1.33 Kg/l (depending on colour)
Coverage (UNE 48282)	9 - 12 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	1 - 2 hours
Recoat time at 23°C 60% RH (UNE 48283)	6 - 12 hours
Methods of Application	Brush, roller and spray-gun.
Thinning	Water
Equipment Cleaning	Water
Application Temperature, RH<80%	+10°C - +30°C
Pack sizes	100 ml and 250 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Thoroughly stir the contents in the pack. The surfaces to be painted have to be clean, dry and suitably primed. Wait at least 5 days before using the painted surface as a writing board.

BARE SURFACES:

Bare canvas: Apply one or two coats of TITAN Gesso Universal Primer.

Plaster or wood: Apply a full coat of TITAN Sealing Primer or Acualux Gloss Varnish. The right thinning rate for the varnish is 1 part of varnish and 3 parts of water. Finish with one or two coats of Acualux TITAN.

Other surfaces : Seek advice.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, softly sand and directly apply Acualux TITAN.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

If they are in poor condition, thoroughly remove them and proceed as on non prepared surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2015-06

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

099 - ACUALUX TITAN

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

