

# ACRYLIC GOYA ESTUDIO



**Product Code:** 09M



## Description

Paint for artists based on 100% acrylic resin and high quality pure pigments. Solid lightfast colours. It can be applied on a wide variety of porous surfaces (canvas, wood, cardboard, etc.) Special effects can be obtained by mixing this paint with TITAN Auxiliary Products for Acrylics. Quick-drying. Water-soluble.

## Fields of Application

Generally speaking, acrylic colours are used for paintings on linen, cotton or other types of canvases, but they can also be applied on any grease-free surface that has been previously prepared.

## Technical Data

|   |   |
|---|---|
| <b>Product Type</b>                       | Acrylic   |
| <b>Finish</b>                             | Satin   |
| <b>Colour (UNE EN ISO 11664-4)</b>        | Range of 40 shades  |
| <b>Density (UNE EN ISO 2811-1)</b>        | 1.10 - 1.31 Kg/l (depending on colour)  |
| <b>Drying at 23°C 60 % RH (UNE 48301)</b> | 30 minutes (If you wish to delay the drying time by 5 - 10 minutes, mix the paint with 5% Acrylic Drying Retarder). |
| <b>Methods of Application</b>             | Brush or spatula  |
| <b>Thinning</b>                           | Water   |
| <b>Equipment Cleaning</b>                 | Water   |
| <b>Pack sizes</b>                         | Tubes: 125ml and 230 ml. Pots: 500 ml   |

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

On clean surfaces, dry and free of grease and suitably primed .

Surface preparation:

Bare canvas: One or two coats of Gesso TITAN Universal Primer.

Plaster or wood: TITAN Sealing Primer or TITAN Gesso.

Other surfaces: Seek advice.

Method of application: Apply a layer with a maximum thickness of 5 mm, with the aid of a paintbrush, spatula or another suitable tool. Thickness above 5 mm is not recommended since it can damage the paint film.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2014-09

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

**TITAN**

09M - ACRYLIC GOYA ESTUDIO

**INDUSTRIAS TITAN S.A.U.**

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

