

INVISIBLE WATER REPELLENT A95



Product Code: 106 0003

Description

Clear and transparent solution. When drying, it does not make any film. It does not change the surface natural appearance. Surface remains breathable (microporous). It protects from the penetration of rain water. After 7 days from application, it allows overcoating with an extensive range of finishing coats. A previous test is necessary in every case.

If applied up to saturation, it prevents the efflorescences that appear on façades due to capillarity in areas with contaminated groundwater levels and close to the ground.

It also helps to maintain façades free from dust and dirt.

Fields of Application

Stone façades and walls, brick-work, concrete and , generally speaking, the whole neutral and alkaline materials commonly used in construction.

Technical Data

Product Type	Emulsion of alkyl polysiloxane
Finish	It does not alter the surface appearance
Colour (UNE EN ISO 11664-4)	Clear
Density (UNE EN ISO 2811-1)	1.00 - 1.04 Kg/l
Coverage (UNE 48282)	3 - 10 m ² /l depending on the surface.
Recoat time at 23°C 60% RH (UNE 48283)	Minimum: 7 days
Methods of Application	Brush, roller and spray-gun
Thinner	Ready-to-use
Equipment Cleaning	Water
Application Temperature, RH<80%	+10°C - +30°C
Volume Solids (UNE EN ISO 3233-3)	4 - 5 %
Pack sizes	4 l and 750 ml

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Thoroughly stir the contents in the pack. The surfaces have to be clean, dry and sound.

Only in vertical or very inclined surfaces, the utmost efficiency with this kind of treatments is to be reached.

If it has rained, wait at least 24 hours before application. If cleaned with high pressure water jet, wait 3 days before the application.

When applying it on recently worked surfaces or new buildings, it is recommended to wait a month before the treatment.

BARE SURFACES:

On unsound, dusty or crusted surfaces, it is necessary to remove by brush the particles with poor adhesion. It is recommended to fill up cracks of more than 0.5 m/m. with filler. mortar, etc.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2017-04

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

106 0003 - INVISIBLE WATER REPELLENT A95

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

