

MULTI PURPOSE LIQUID STRIPPER

TITAN

Product Code: 113

Description

Liquid stripper without methylene chloride, very energetic and quick to apply. For any surface, either varnished or painted. Its low viscosity allows reaching any corner of the piece. Its studied formulation is highly respectful of wood.

Fields of Application

Suitable for effortless removal of varnishes and paints generally used in: Furniture for a few minutes restoration, decorative elements of carpentry both indoors and outdoors, cleaning work tools, in the which there are no plastic parts sensitive to solvents. In general, any structure that needs to be stripped.

Technical Data

Density (UNE EN ISO 2811-1)	1.00 - 1.05 Kg/l
Coverage	5 - 7 m ² /l
Methods of Application	Brush
Pack sizes	4 l and 1 l

Directions for use

GENERAL REMARKS:

Scratching the surfaces with coarse sandpaper or scraper, a stronger effect will be achieved on surfaces which are difficult to get stripped.

Apply by brush a thick and uniform layer, without insisting, Leave the product to act for the time required to soften the paint (from 3 to 30 minutes). Remove it easily by means of a scraper. On moulding areas use Steel Wool 00 TITAN Woodwork. Do not let the stripper dry on the surface.

Very hard or thick layers of paint may require a second application of Liquid Stripper.

Before repainting surfaces that were treated with Liquid Stripper, they have to be cleaned with solvent, in order to achieve perfect adherence of the new paint to the substrate.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Carefully open the container and use safety glasses.

Issue date: 2019-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona (España)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

