

TITAN GEL STRIPPER

TITAN



Product Code: 114

Description

Jelly-type, quick and effective paint stripper. Free from methylene chloride Easy application. Non-drip because of its jelly consistency.

Coverage may be doubled and even tripled, depending on circumstances, by spreading again some used paint stripper with a scraper on the coating to be removed.

Fields of Application

For effortless elimination, in a few minutes, of any kind of oil-based, alkyd, cellulose, emulsion, vinyl, chlorinated rubber, silicone or epoxy coatings. Very useful for cleaning brushes and rollers provided they are not made out of nylon or rubber.

Technical Data

Density (UNE EN ISO 2811-1)	1.00 - 1.05 Kg/l
Coverage	4 - 5 m ² /l
Methods of Application	Brush
Pack sizes	4 and 1 l

Directions for use

GENERAL REMARKS:

Improved results and a more effective action will be obtained by sanding the surfaces with grit sandpaper or a scraper. Apply by brush one thick and uniform coat. Avoid too many brush strokes. Allow the necessary time for the product to soften old coating (from 3 to 30 minutes). Then remove the residue with scraper, metallic brush or any other suitable tool. Old coatings will become detached easily. Do not let the Gel Stripper get dry on the paint.

Very hard or thick old covering may require a new application of Gel Stripper.

Before painting again stripped surfaces, clean them with solvent to ensure perfect adhesion of the new paint.

Painted plastics may get softened in contact with the Gel Stripper. Test previously.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

Open the can carefully and use security glasses.

Issue date: 2015-05

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

