

T4 VINYL PAINT

Indoor . Matt

TITAN



Product Code: 121

Description

High quality, high covering, wash resistant emulsion paint. Silky matt finish. Permanent, pure white. Easy application. Hard wearing. It contains anti-mould preservative.

Technical Data

Product Type	Vinyl Veova
Finish	Matt
Colour (UNE EN ISO 11664-4)	White + TITANCOLOR Bases: Intermediate and Neutral
Density (UNE EN ISO 2811-1)	1.45 - 1.50 Kg/l
Coverage	10 - 12 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	20 - 60 minutes
Recoat time at 23°C 60% RH (UNE 48283)	6 - 8 hours
Methods of Application	Brush, roller and spray-gun.
Thinner	Water
Application Temperature, RH<80%	+10°C - +30°C
Tinting	TITAN Universal Tinting Colours or TITANCOLOR System
Volume Solids (UNE EN ISO 3233-3)	37 - 38 %
VOC (UNE EN ISO 11890-2)	2004/42/IIA (a) (75/30) Max. VOC 15 g/l
Pack sizes	15 l , 4 l and 1 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Certificates

Reaction to Fire UNE EN 13501-1:2007+A1:2010: B-s1,d0 on B-s1,d0 surfaces.

Determination of contrast ratio (Hiding Power) UNE EN ISO 6504-3: Class 2. 9.4 m²/l (98% hiding power)

Wet-scrub resistance UNE EN ISO 11998: Class 2 washability

Directions for use

GENERAL REMARKS:

Carefully stir the contents in the pack. The surfaces to be painted have to be clean, dry and in good condition.

BARE SURFACES:

If they are in good condition, apply a first coat thinned with 10 - 15% water. Apply a second unthinned coat.

If the surfaces are in poor condition, repair all the damaged areas. Remove old paints as well as all poorly adhered or

inconsistent material. Clean dirt and existing dust.

In order to strengthen the surface and achieve uniform porosity, as well as on distemper, size, lime paintings, or where they have been removed, previously apply a base coat of TITAN Sealing Primer or Fixative.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

After prior washing and sanding, directly apply a first coat thinned with 10 - 15% water. Apply a second unthinned coat.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Thoroughly remove all previous paint coats and proceed as for non-prepared surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Store in tightly closed containers protected from sources of heat and temperatures below 0°C. Shelf life: 36 months in original unopened packaging.

Waste management: Follow local legal regulations. Help to protect the environment, do not empty into drains, dispose of this material and its container at hazardous or special waste collection points. Calculate the amount of product you will need to avoid waste and extra costs. Collect the leftover material and keep it well stored for a new use.

It contains BCM, IPU, IPBC, Terbutryn, to protect the initial properties of the treated article.

Issue date: 2020-11

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



Akzo Nobel Coatings, S.L.U – Carrer Feixa Llarga, 14-20 - Pol. Ind. Zona Franca 08040 Barcelona
(Espanya)
Teléfono 934 842 500
Ins. Reg. Mer. de Barcelona T. 47631, F- 95, H. nº B-45052, Inscrp. 210
N.I.F. B-08218158

