

# MULTI PLASTER PAINT A22

Indoor . Matt



Product Code: 122

## Description

Matt, vinyl high-covering emulsion paint,. To be used in indoor walls and ceilings. Especially recommended for surfaces made out of projection gypsum or plasterboards. Excellent whiteness, high opacity and good adhesion.

## Technical Data

<b>Product Type</b>	Vinyl versatate
<b>Finish</b>	Matt
<b>Colour (UNE EN ISO 11664-4)</b>	White
<b>Density (UNE EN ISO 2811-1)</b>	1.62 - 1.66 Kg/l
<b>Coverage (UNE 48282)</b>	6 - 9 m <sup>2</sup>
<b>Drying at 23°C 60 % RH (UNE 48301)</b>	30 - 60 minutes
<b>Recoat time at 23°C 60% RH (UNE 48283)</b>	6 - 8 hours
<b>Methods of Application</b>	Brush, roller and spray-gun.
<b>Thinner</b>	Water
<b>Application Temperature, RH&lt;80%</b>	+10°C - +30°C
<b>Tinting</b>	TITAN Universal Tinting Colours or TITAN Professional Water-Based Dye
<b>Volume Solids (UNE EN ISO 3233-3)</b>	46 - 47 %
<b>VOC (UNE EN ISO 11890-2)</b>	2004/42/IIA (a) (75/30) Max. COV 20 g/l
<b>Pack sizes</b>	15 l and 4 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

## Directions for use

### GENERAL REMARKS:

Carefully stir the contents in the pack. The surfaces to be painted have to be clean, dry and sound.

### BARE SURFACES:

If the surfaces are in good condition, apply a first coat thinned with 10 - 15% water. Apply a second unthinned coat.

If the surfaces are in poor condition, repair all the damaged areas, remove all poorly adhered particles and material. Clean all existing dirt and dust.

In order to homogenise porosity and improve the finish, as well as on distemper and size paints, whitewash or the surfaces where these have been removed, it is recommended to apply a first coat of A19 Water based Fixative or A18 Water based Sealing Primer.

## Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Protect the packs from temperatures below 0°C

Issue date: 2018-07

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

**TITAN**

122 - MULTI PLASTER PAINT A22

### INDUSTRIAS TITAN S.A.U.

**España:** P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

**Portugal:** Rua Fonte Cova, 51 - 4475-031 Maia  
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia  
T. +351 229 865 450 - F. +351 229 810 764

