

ACRYLIC EMULSION PAINT TP23

Indoor. Matt



Product Code: 123

Description

Emulsion paint. For decorating indoor walls and ceilings. Easy-to-apply. Breathable. It does not alter permeability and therefore, it allows water vapour going through the surface. Snow white. Good coverage. It contains anti-mould preservative of the paint film.

Technical Data

Product Type	Acrylic styrene.
Finish	Matt
Colour (UNE EN ISO 11664-4)	White
Density (UNE EN ISO 2811-1)	1.50 - 1.56 Kg/l
Coverage (UNE 48282)	7 - 10 m ² /l (70 - 80 dry μ)
Drying at 23°C 60 % RH (UNE 48301)	20 - 40 minutes
Recoat time at 23°C 60% RH (UNE 48283)	6 hours.
Methods of Application	Brush, roller and spray-gun.
Thinner	Water
Recommended Thickness (UNE EN ISO 2808)	140 - 160 dry μ in two coats
Tinting	TITAN Universal Tinting Colours, Professional Water-Based Dye or Servicolor System
Volume Solids (UNE EN ISO 3233-3)	38 - 39 %
VOC (UNE EN ISO 11890-2)	2.004/42/IIA (a) (75/30) Max. COV 18 g/l
Pack sizes	20 l, 15 l, 10 l, 4 l and 1 l. Rectangular bucket: 10 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Certificates

Determination of contrast ratio (Hiding Power) UNE EN ISO 6504-3: 7.3 m²/l (98% hiding power) CLASS 2

Wet-scrub resistance UNE EN ISO 11998: Class 3

Reaction to Fire: UNE EN 13501-1:2007+A1:2010 Standard: B-s1, d0

VOC emission ISO 16000-6:2006: A+

Directions for use

GENERAL REMARKS:

Carefully stir the contents in the pack. The surfaces to be painted have to be clean, dry and sound.

BARE SURFACES:

If the surfaces are in good condition, apply a first coat thinned with 10 - 15% water. Apply a second unthinned coat.

If the surfaces are in poor condition, repair all the damaged areas, remove all poorly adhered particles and material. Clean all existing dirt and dust.

In order to homogenise porosity and improve the finish, as well as on distemper and size paints, whitewash or the surfaces where these have been removed, it is recommended to apply a first coat of TITAN Sealing Primer or Fixative.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Directly apply the paint after previous washing or brushing. Thin the first coat with 10 - 15% water. Apply a second unthinned coat.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Thoroughly remove old paint coats and proceed as for bare surfaces.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

It contains BCM, IPU, IPBC, Terbutrina, to protect the initial properties of the treated article.

Protect the packs from temperatures below 0°C

Issue date: 2017-06

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.



TITAN

123 - ACRYLIC EMULSION PAINT TP23

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

