

POLYURETHANE VARNISH D9

For Wooden Floors. Indoor. Gloss



Product Code: 137

Description

Easy to apply polyurethane varnish. Very hard and flexible. Long lasting and high resistance to wear.

Fields of Application

Especially suitable for indoor pine wood floors. Smooth, long-lasting and elastic finish. It is also suitable for panelling, furniture, etc.

Technical Data

Product Type	Urethaned oil
Finish	Gloss
Colour (UNE EN ISO 11664-4)	Clear
Density (UNE EN ISO 2811-1)	0.88 - 0.92 Kg/l
Coverage (UNE 48282)	13 - 16 m ² /l
Drying at 23°C 60 % RH (UNE 48301)	3 - 4 hours
Recoat time at 23°C 60% RH (UNE 48283)	18 - 24 hours
Methods of Application	Brush or roller
Equipment Cleaning	TITAN Synthetics Thinner or White Spirit
Application Temperature, RH<80%	+ 10°C - +30°C
Tinting	TITAN Universal Tinting Colours
Flash Point (UNE EN ISO 3679)	43 °C
Volume Solids (UNE EN ISO 3233-3)	43 - 44 %
VOC (UNE EN ISO 11890-2)	2.004/42IIA (i) (600/500) Max. COV 500 g/l
Pack sizes	10 l and 4 l

Variations in temperature, humidity, thickness, tinting or surface type, etc. may lead to changes in drying, in coverage or in other properties.

Directions for use

GENERAL REMARKS:

Thoroughly stir the contents in the pack. Apply by thin coats, following the wood grain, on thoroughly smooth (sanded), clean and dry surfaces.

Tropical or resinous wood: Please refer to the Technical Service.

Wait 24 hours before stepping on the surface.

BARE SURFACES:

Clean with thinner eventual spots of oil, paint or wax, and lightly sand wood. Dust off and apply one thin coat. After 24 hours,

lightly sand, dust off and apply a second coat.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN GOOD CONDITION:

Wash, lightly sand and directly apply.

MAINTENANCE OF PREVIOUSLY COATED SURFACES IN POOR CONDITION:

Remove unsound previous varnish coats and proceed as for bare wood.

Precautions

Always read the pack label before use. For more information, please refer to the Safety Data Sheet.

Issue date: 2015-02

Any technical sheet is automatically cancelled by a subsequent sheet or five years after the issue date. We guarantee the quality of our products. However, we disclaim any liability in relation to factors other than the coating itself or in relation to an unsuitable use or application method. In case of doubt, please refer to our technical service before applying the products.

TITAN

137 - POLYURETHANE VARNISH D9

INDUSTRIAS TITAN S.A.U.

España: P. I. Pratenc, c/ 114, 17-19 - 08820 El Prat de Llobregat- T. +34 93 479 74 94

Portugal: Rua Fonte Cova, 51 - 4475-031 Maia
Endereço Postal: Apartado 2020 - 4476-909 Castelo da Maia
T. +351 229 865 450 - F. +351 229 810 764

